

AN INVESTIGATION OF MERCURY AS A
HIGH-SPEED ELECTRICAL CONTACT

R. G. SHULTS

THESIS
S49

Library
United Naval Postgraduate School
Monterey, California

229

APPENDIX

DISCUSSION

CONCLUSIONS

RESULTS &
DISCUSSION

EQUIPMENT
PROCEDURE

This work is accepted as fulfilling the
thesis requirements for the degree of Master
of Science in Electrical Engineering from the

United States Naval Postgraduate School.

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

R. G. SHULTS

COMMITTED IN PARTIAL FULFILLMENT
OF THE REQUIREMENTS FOR THE DEGREE OF
MASTERS OF SCIENCE

UNIVERSITY OF CALIFORNIA, SAN DIEGO
La Jolla, California

1962

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

R. G. SHULTS

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

By

R. G. SHULTS
Commander, United States Navy

SUBMITTED IN PARTIAL FULFILLMENT
OF THE REQUIREMENTS FOR THE DEGREE OF
MASTER OF SCIENCE

United States Naval Postgraduate School
Monterey, California

1952

Thesis
59

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

By

R. G. SHULTS
Commander, United States Navy

MASTER OF SCIENCE
OF THE REQUIREMENTS FOR THE DEGREE OF
SUBMITTED IN PARTIAL FULFILLMENT

United States Naval Postgraduate School
Monterey, California

1952

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

Preface

The use of carbon as a medium for transferring electrical currents between two pieces of copper moving at different, and often high, relative speeds is a long-established and adequately successful practice; that is, it is a practice successful at sea level and at the lower altitudes. The growth of the electrical load in aircraft, coupled with its ability to reach ever-increasing altitudes has led to failure of the standard carbon brushes. The reasons for the failure of carbon brushes at high altitudes are not well known, but are believed due to the deterioration of the lubricating qualities of standard air at the higher altitudes. The nature of the carbon brush failure is an accelerated wearing away of the brush in a matter, sometimes, of minutes, whereas at sea level it might have lasted for years at the same speed and current density.

In recent months much has been done to increase the life of the carbon brush at high altitudes. One manufacturer reports a specially impregnated carbon brush with a high altitude life of some 750 hours. On the other hand, certain of the steps taken to make the carbon brush more durable at high altitudes have rendered it short-lived at the lower

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

Preface

The use of carbon as a medium for transferring electrical currents between two pieces of copper moving at different, and often high, relative speeds is a long-established and adequately successful practice; that is, it is a practice successful at sea level and at the lower altitudes. The growth of the electrical load in aircraft, coupled with its ability to reach ever-increasing altitudes has led to failure of the standard carbon brushes. The reasons for the failure of carbon brushes at high altitudes are not well known, but are believed due to the deterioration of the lubricating qualities of standard air at the higher altitudes. The nature of the carbon brush failure is an accelerated wearing away of the brush in a matter, sometimes, of minutes, whereas at sea level it might have lasted for years at the same speed and current density. In recent months much has been done to increase the life of the carbon brush at high altitudes. One manufacturer reports a specially impregnated carbon brush with a high altitude life of some 750 hours. On the other hand, certain of the steps taken to make the carbon brush more durable at high altitudes have rendered it short-lived at the lower

altitudes. A comprehensive review of the high-altitude carbon brush-dusting problem may be found in Ref. 1.

As a partial answer to the problem, this investigation was initiated. Reasoning was along these lines: If a solid type of brush is troublesome, could a liquid type, of necessity enclosed, be designed to be less troublesome? The liquid, of course, should be a good conductor, should be easy to handle and contain, should be readily available, but need not necessarily be inexpensive if it could eliminate electrical power failure in modern military aircraft now caused by carbon brush dusting.

A good many fluid conductors of electricity immediately suggested themselves, but one of the best and most common, the fluid metal mercury, was almost an obvious first choice, particularly since Faraday had suggested its use in connection with the homopolar machine (see Ref. 2).

As a first step then, in August 1951 an idea for a test vehicle was sketched and presented to Professor C. V. O. Terwilliger, Head of the Electrical Engineering Department of the U. S. Naval Postgraduate School, then at Annapolis, Maryland. Dr. Terwilliger considered the idea worthy of thesis investigation as part of the requirements leading to the award of a Master's Degree in Electrical Engineering. Consequently, the device was designed and built at Annapolis, being completed by mid-November 1951.

Due to the moving of the Postgraduate School to Monterey, California in late November 1951, actual testing was delayed

altitudes. A comprehensive review of the high-altitude carbon

brush-dusting problem may be found in Ref. 1.

As a partial answer to the problem, this investigation was initiated. Reasoning was along these lines: If a solid type of brush is troublesome, could a liquid type, of necessity enclosed, be designed to be less troublesome? The liquid, of course, should be a good conductor, should be easy to handle and contain, should be readily available, but need not necessarily be inexpensive if it could eliminate electrical power failure in modern military aircraft now caused by carbon brush dusting.

A good many fluid conductors of electricity immediately suggested themselves, but one of the best and most common, the liquid metal mercury, was almost an obvious first choice, particularly since Tarasay had suggested its use in connection with the homopolar machine (see Ref. 2).

As a first step then, in August 1951 an idea for a test vehicle was sketched and presented to Professor G. V. O. Terwilliger, Head of the Electrical Engineering Department of the U. S. Naval Postgraduate School, then at Annapolis, Maryland. Dr. Terwilliger considered the idea worthy of thesis investigation as part of the requirements leading to the award of a Master's Degree in Electrical Engineering. Consequently, the device was designed and built at Annapolis, being completed by mid-November 1951.

Due to the moving of the Postgraduate School to Monterey, California in late November 1951, actual testing was delayed

until April 1952. The nature of the testing and the results obtained are herein set forth.

It is at once apparent that a fluid brush would not be compatible with a commutator; hence, it was considered only for its use with a slip-ring. In this connection, then, one must keep in mind that even though the fluid brush might be successful in solving the high-altitude brush problem, it would eliminate the commutator and make necessary the employment of the homopolar machine either for main direct current generation or for dc excitation for the alternator. Thus, a secondary problem arose requiring investigation: could the extra weight and size, if any, of the homopolar machine be tolerated?

Because time ran out and because this investigation and a report of it had of necessity to be completed by June 1952, the mercury brush was little more than made ready for a sea-level test and the secondary problem was not approached at all.

Thus there remains considerable investigation at sea level, and the total investigation in an altitude chamber, plus any flight testing which might ultimately be indicated.

It follows that the success or failure of mercury need not preclude further investigation of the many other fluid conductors, nor of the homopolar generator as an exciter, for other reasons.

until April 1952. The nature of the testing and the results obtained are herein set forth.

It is at once apparent that a fluid brush would not be compatible with a commutator; hence, it was considered only for its use with a slip-ring. In this connection, then, one must keep in mind that even though the fluid brush might be successful in solving the high-altitude brush problem, it would eliminate the commutator and make necessary the employment of the homopolar machine either for main direct current generation or for dc excitation for the alternator. Thus, a secondary problem arose regarding investigation: could the extra weight and size, if any, of the homopolar machine be tolerated? Because time ran out and because this investigation and a report of it had of necessity to be completed by June 1952, the mercury brush was little more than made ready for a sea-level test and the secondary problem was not approached at all.

Thus there remains considerable investigation at sea level, and the total investigation in an altitude chamber, plus any flight testing which might ultimately be indicated.

It follows that the success or failure of mercury need not preclude further investigation of the many other fluid conductors, nor of the homopolar generator as an exciter, for other reasons.

R. A. Shultz

CDR R. A. Shultz, USN
 Section AED
 U. S. Naval Postgraduate School
 Monterey, California
 June, 1952

CONTENTS

List of Tables.	vi
List of Illustrations	v
Preface	i
Summary	vii
Equipment	i
Procedure	8
Results	11
Discussion.	14
Conclusions	21
Recommendations	22
References.	24
Appendix	
A. Laboratory Log	57
B. Excerpts From Liquid Metals Handbook	71

CONTENTS

vi	List of Tables
v	List of Illustrations
i	Preface
vi	Summary
i	Equipment
8	Procedure
vi	Results
14	Discussion
21	Conclusions
21	Recommendations
24	References

Appendix

57	A. Laboratory Log
	B. Excerpts from Liquid Metals
71	Handbook

LIST OF ILLUSTRATIONS

1.	Mercury Brush Detail Drawing.	76
2.	Photograph of Test Device	43
3.	Photograph of Test Device	44
4.	Calibration Curve, Brush Current Ammeter. . .	45
5.	Calibration Curve, Brush Drop Voltmeter . . .	46
6.	Calibration Curve, Carbon Drop Voltmeter. . .	47
7.	Photograph of Apparatus	48
8.	Photograph of Apparatus	49
9.	Curve of Current Densities.	50
10.	Conversion Chart: RPM to FPS.	51
11.	Conversion Chart: RPM to FPS.	52
12.	Brush Drop Vs. Contact Speed: Test's 5-19 . .	53
13.	Brush Drop Vs. Contact Speed: All Tests . . .	54
14.	Brush Drop Vs. Current.	55
15.	Brush Drop Vs. Time: Test No. 21	56

LIST OF ILLUSTRATIONS

1.	Mercury Brush Detail Drawing.	76
2.	Photograph of Test Device	43
3.	Photograph of Test Device	44
4.	Calibration Curve, Brush Current Ammeter.	45
5.	Calibration Curve, Brush Drop Voltmeter	46
6.	Calibration Curve, Carbon Drop Voltmeter.	47
7.	Photograph of Apparatus	48
8.	Photograph of Apparatus	49
9.	Curve of Current Densities.	50
10.	Conversion Chart: RPM to FPS.	51
11.	Conversion Chart: RPM to FPS.	52
12.	Brush Drop Vs. Contact Speed: Test's 5-19	53
13.	Brush Drop Vs. Contact Speed: All Tests	54
14.	Brush Drop Vs. Current.	55
15.	Brush Drop Vs. Time: Test No. 21	56

LIST OF TABLES

	<u>Page</u>
I. Results of Test No. 5.	25
II. Results of Test No. 6.	26
III. Results of Test No. 7.	27
IV. Results of Test No. 8.	28
V. Results of Test No. 9.	29
VI. Results of Test No. 10	30
VII. Results of Test No. 11	31
VIII. Results of Test No. 12	32
IX. Results of Test No. 13	33
X. Results of Test No. 14	34
XI. Results of Tests No. 15 & 16.	35
XII. Results of Tests No. 17, 18 & 19 . . .	36
XIII. Results of Test No. 20.	37
XIV. Results of Test No. 21.	38
XV. Results of Tests No. 22 & 23.	39
XVI. Summary of Tests No. 20, 21, 22, & 23.	40
XVII. Temperature Rise Summary of All Tests.	41
XVIII. Some Physical Properties of Mercury, Iron, Copper	42

LIST OF TABLES

I.	Results of Test No. 5.	25
II.	Results of Test No. 6.	26
III.	Results of Test No. 7.	27
IV.	Results of Test No. 8.	28
V.	Results of Test No. 9.	29
VI.	Results of Test No. 10.	30
VII.	Results of Test No. 11.	31
VIII.	Results of Test No. 12.	32
IX.	Results of Test No. 13.	33
X.	Results of Test No. 14.	34
XI.	Results of Tests No. 15 & 16.	35
XII.	Results of Tests No. 17, 18 & 19.	36
XIII.	Results of Test No. 20.	37
XIV.	Results of Test No. 21.	38
XV.	Results of Tests No. 22 & 23.	39
XVI.	Summary of Tests No. 20, 21, 22, & 23.	40
XVII.	Temperature Rise Summary of All Tests.	41
XVIII.	Some Physical Properties of Mercury.	42
	Iron, Copper.	43

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

Summary

In seeking a possible substitute for the carbon brush for aircraft use, the idea of using mercury as a fluid contact was investigated.

It was found that a mercury-steel combination appeared to be satisfactory electrically at sea level.

It was further found that the voltage drop across the moving mercury-steel contact appeared to be *independent* of the current flow through the contact and of the relative speed of the contact surfaces.

INSTRUCTIONS TO
JURY
IN THE CASE OF
THE PEOPLE vs. JOHN D. BROWN

Charge

The first question for you to decide is whether or not the
evidence shows that the defendant was guilty of the crime
charged. If you find that the evidence does show that the
defendant was guilty, you must then decide whether or not
the law requires that he be punished. If you find that the
evidence does show that the defendant was guilty, and that
the law requires that he be punished, you must then decide
what punishment should be given. You must decide whether or
not the punishment should be death, or imprisonment for
life, or imprisonment for a term of years, or a fine, or
some other punishment. You must decide what punishment
should be given.



No. 4780SI
Colored Tabs

No. 4781SI
Clear Tabs

MADE IN U. S. A.

NATIONAL INSERTABLE-TAB INDEXES ENABLE YOU TO
MAKE YOUR OWN SUBJECT ARRANGEMENT, USING PLAIN
INSERTS ON WHICH TO WRITE YOUR OWN CAPTIONS.

EQUIPMENT &
PROCEDURE

AN INVESTIGATION OF
MERCURY
AS A
HIGH-SPEED ELECTRICAL CONTACT

Equipment

A fluid conductor brush must take the general form of two solid conductors separated by the fluid in order to permit relative motion. A typical usage would find one of the solid conductors fixed; the other moveable. While an experimental design along these lines would have been preferred as simulating actual conditions more closely, but because it was desired that its performance at high peripheral speeds be known, the mercury brush was designed so that both solid conductors could move in opposite directions. This led to unsatisfactory operating conditions at high speeds as will be pointed out later.

Consequently, the test mercury brush as built took the form of a steel disc rotating in a pool of mercury contained in a steel cylinder rotating in the opposite direction. The use of steel in the presence of mercury was again an almost obvious first choice, since mercury dissolves all common metals as amalgams except iron, platinum and nickel.

Concerning the size to make the test brush there was little to go on, and it was decided to keep it fairly small since if it should bust for any reason, the danger to those

THE UNIVERSITY OF
CHICAGO
IN
THE HISTORY OF THE
UNION

CHICAGO

1900

It was the first time that the University of Chicago
had ever been mentioned in the title of a book.
The book was published in 1892, and it was the first
time that the University of Chicago had ever been
mentioned in the title of a book. The book was
published in 1892, and it was the first time that
the University of Chicago had ever been mentioned
in the title of a book. The book was published in
1892, and it was the first time that the University
of Chicago had ever been mentioned in the title of
a book. The book was published in 1892, and it
was the first time that the University of Chicago
had ever been mentioned in the title of a book.

The book was published in 1892, and it was the first
time that the University of Chicago had ever been
mentioned in the title of a book. The book was
published in 1892, and it was the first time that
the University of Chicago had ever been mentioned
in the title of a book. The book was published in
1892, and it was the first time that the University
of Chicago had ever been mentioned in the title of
a book. The book was published in 1892, and it
was the first time that the University of Chicago
had ever been mentioned in the title of a book.
The book was published in 1892, and it was the
first time that the University of Chicago had ever
been mentioned in the title of a book. The book
was published in 1892, and it was the first time
that the University of Chicago had ever been
mentioned in the title of a book. The book was
published in 1892, and it was the first time that
the University of Chicago had ever been mentioned
in the title of a book. The book was published in
1892, and it was the first time that the University
of Chicago had ever been mentioned in the title of
a book. The book was published in 1892, and it
was the first time that the University of Chicago
had ever been mentioned in the title of a book.

about it would be greatly minimized. As a further consideration, ready-made drive shafting and matching bearings with pedestals were immediately available and were of such size that a large mercury brush was inadvisable. In order to further reduce danger due to busting, the walls of the cylinder were made much thicker than necessary. This also led to an operational problem to be pointed out later.

It was necessary to provide some sort of seal about the entering disc shaft to prevent any tendency for the mercury to leak. This took the form of a close-fitting machined-pressed paper insert, screwed to the cylinder face. This, too, proved a troublesome spot until late in the test period.

To provide for interim inspection of the interior of the brush, the shell of the cylinder was made so that it could be unscrewed and the disc withdrawn. This feature also proved a problem at high speeds and although never solved in this series of tests, its solution would be no problem in future tests, as will be pointed out.

Since mercury boils at sea level at about 356.9° C. and since it was not known what the heat generation might be in the brush, it was thought necessary that some means of recording temperature be provided. This was effected by drilling out the center of the two drive shafts to permit insertion of thermometers. This feature proved very helpful and gave no trouble directly, although it contributed to a hot-spot

problem, as will be pointed out. The sensitive elements of the thermometers were thus placed almost at the center of the brush.

To provide a means of driving the two elements of the brush, two 4-step cone pulleys were mounted on the shaft to be belt-driven by two D.C. motors. These motors were Marathon Electric 1/8 HP, shunt-wound, 115 V, 1.3a, 1725 rpm, type DS motors. To provide speed control in addition to that inherent in the pulleys, rheostats, 100 ohms and 800 ohms, respectively, were placed in both armature and field circuits of the driving motors. This feature permitted excellent speed control throughout the test period.

To get current to the mercury brush since it was not a part of any sort of generating device and because both parts of it rotated, it was necessary to resort to carbon brushes and brass slip rings--brass because copper was not available and because the phenomena occurring at the carbon brushes would have no effect on the mercury brush anyway. To this extent, a sort of loose comparison of the two brushes unfolded as they operated side-by-side under identical conditions during the tests. Carbon brushes and holders were salvaged from an aged surveyed repulsion-induction motor and a mounting bracket of bakelite was fashioned to permit two carbon brush sets to operate in parallel on each of the two brass slip rings. This arrangement proved entirely satisfactory.

The apparatus in its entirety was mounted on a large steel plate to provide dimensional stability and mechanical damping.

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

...the ... of ... the ... of ...

This, too, was most satisfactory. It was at once obvious, however, that if the drive shafts were to be current conductors, insulation from this steel plate was necessary. This was easily accomplished by mounting the bearing pedestals on pressed paper, by mounting the pulleys on pressed paper sleeves, by using non-conducting v-belts, by setting the carbon brush holders in bakelite as already mentioned and by using insulating tape to keep the thermometers from rotating. At no time during the tests did grounds develop.

To provide a uniform length of path for current flow through the mercury, the disc edge was made circular in cross-section and the interior of the cylinder was so machined that the distance from the disc to the cylinder was $1/8$ " in all directions. There was no particular reason for this gap length; further tests would surely establish an optimum.

The test mercury brush as described thus far was designed by the investigator and built by Mr. Joseph Octavek of the Machine Shop Section of the Postgraduate School. It must be pointed out here that the failures which occurred were faults of design, whereas the ability of the device to withstand testing as it did was a credit to the great care which Mr. Octavek exercised in putting the device together. The drawing from which it was built and assembled appears as Fig. 1, placed at the back of the report because of its large size. A close-up photograph of the brush assembly is shown by Fig. 2.

Although the Postgraduate School resumed classes in February 1952, tests were delayed because of lack of power at the laboratories. When 3-phase AC power did become available, DC power also became available from any one of a number of motor-generator sets in the laboratory. This was thus the source of power. Voltage for the driving motors was taken from the house DC bus. An independent M-G set was operated to supply DC power to a standard load resistor bank which was fed through the test brush assembly. In this way, variation of load on the test brush could have no effect on the driving motor voltage and thus made for better speed control as well as load control.

The load resistor bank consisted of three separate banks, each of 24 amperes capacity at 125 volts, connected in parallel to provide up to 72 amperes. The generator feeding the load bank was rated at 110 volts, 59 amperes. To keep the carbon brush current density below 50 amperes per square inch, no more than 48 amperes were ever fed through the brushes.

To provide forced ventilation since the presence of mercury vapor was a distinct possibility, two ordinary 18" fans were provided. It later developed that by placing one of the fans quite close to the brushes, enough cooling was provided to permit extension of the tests.

In addition to the thermometers, which were Weston Model 226 calibrated from 0 degrees C. to 200 degrees C., other measuring devices were provided as follows.

Published weekly, except on Sundays, by the American Medical Association, 535 North Dearborn Street, Chicago, Ill. 60610.
Subscription price, \$5.00 per annum in advance. Single copies, 15 cents.
Entered as second-class matter, May 2, 1912, under Post Office No. 384, at Chicago, Ill., under special agreement of the Post Office and General Office.
Acceptance for mailing at special rate of postage provided for in Section 1103, Act of October 3, 1917, authorized on July 1, 1920.
Postage paid at Chicago, Ill., and at additional mailing offices.
Copyright, 1950, by American Medical Association.
All rights reserved.
Printed at the American Medical Association Press, Chicago, Ill.

Published by the American Medical Association, 535 North Dearborn Street, Chicago, Ill. 60610.
Subscription price, \$5.00 per annum in advance. Single copies, 15 cents.
Entered as second-class matter, May 2, 1912, under Post Office No. 384, at Chicago, Ill., under special agreement of the Post Office and General Office.
Acceptance for mailing at special rate of postage provided for in Section 1103, Act of October 3, 1917, authorized on July 1, 1920.
Postage paid at Chicago, Ill., and at additional mailing offices.
Copyright, 1950, by American Medical Association.
All rights reserved.
Printed at the American Medical Association Press, Chicago, Ill.

To measure rotary speeds of each pulley, two Strobotacs were mounted to flash continuously and directly on the pulleys as shown by Fig. 3, Serial No. 16611 was directed on the disc pulley; Serial No. 16756 on the cylinder pulley. The Strobotacs were of two speed ranges: 600 to 3000 rpm and 2400 to 15000 rpm.

To measure brush current, a Weston Model 45 DC ammeter Serial No. 59320, scale 0 to 50 amperes was placed in series with the brushes. Its calibration curve is given by Fig. 4.

Mercury brush voltage was taken with a General Electric 100,000 ohms per volt DC voltmeter, Serial No. 1112214, scale 0 to 3 volts, whose calibration curve appears as Fig. 5. Picking off the voltage drop across the mercury brush was something of a problem never satisfactorily solved, as will be discussed. Pickoff was provided by two thin brass leaves riding on the inside faces of the two brass slip rings, as shown at points A in Fig. 2.

For no particular reason other than to provide information for the previously mentioned loose comparison of the performance of the carbon brush vs. that of the mercury brush, the drop across the entire brush assembly; i.e., the carbon and mercury in series, was taken by a Westinghouse 5000 per volt DC voltmeter, Serial No. 2357120, scale 0 to 10 volts. Calibration curve for this meter is given by Fig. 6.

The load voltage applied to the brushes was taken by a Westinghouse 5000 ohms per volt DC voltmeter, Serial 2357110, scale 0 to 500 volts. This meter was not calibrated.

Two side views of the complete test assembly are given by Figures 7 and 8. A steel shield, not shown, was provided

to cover the rotating parts during the test--it proved necessary. It did not restrict air-flow from the fans.

THE UNIVERSITY OF CHICAGO
LIBRARY

PROCEDURE

The period 22 April 1952 through 11 May 1952, ten working days, was consumed in readying the device for test. Twenty-three formal tests in which data were taken were conducted from 12 May 1952 through 26 May 1952, actual tests being made on only ten working days of this period. A log of the entire experiment was kept and is included herein as Appendix A.

Test procedure was simple enough. Only three quantities, in general, were permitted to vary. These were:

- (1) Brush Current
- (2) Brush Relative Speed
- (3) Mercury Volume (and hence current density in the mercury)

For each test, readings were recorded of brush load supply voltage and current, voltage drop across the entire (carbon in series with mercury) brush assembly, voltage drop across the mercury brush alone, rpm of each shaft, and temperature at the centers of the disc and of the cylinder. Beginning with Test No. 11, elapsed time readings were taken along with all other readings.

For tests No. 11 through 23, one of the 18" fans was moved to within 12" of the mercury brush as shown clearly by Fig. 3, providing, it was estimated, some one or two inches of water blast air cooling.

Introduction

1900

The first part of the book is devoted to a general survey of the history of the subject. It begins with a brief account of the early attempts to explain the phenomena of life, and then proceeds to a more detailed consideration of the various theories which have been advanced from time to time. The second part of the book is devoted to a critical examination of the most important of these theories, and the third part to a discussion of the present state of the subject and the prospects for the future.

The first part of the book is devoted to a general survey of the history of the subject. It begins with a brief account of the early attempts to explain the phenomena of life, and then proceeds to a more detailed consideration of the various theories which have been advanced from time to time.

- (1) The first part of the book is devoted to a general survey of the history of the subject.
- (2) The second part of the book is devoted to a critical examination of the most important of these theories.
- (3) The third part of the book is devoted to a discussion of the present state of the subject and the prospects for the future.

The first part of the book is devoted to a general survey of the history of the subject. It begins with a brief account of the early attempts to explain the phenomena of life, and then proceeds to a more detailed consideration of the various theories which have been advanced from time to time. The second part of the book is devoted to a critical examination of the most important of these theories, and the third part to a discussion of the present state of the subject and the prospects for the future.

The first part of the book is devoted to a general survey of the history of the subject. It begins with a brief account of the early attempts to explain the phenomena of life, and then proceeds to a more detailed consideration of the various theories which have been advanced from time to time. The second part of the book is devoted to a critical examination of the most important of these theories, and the third part to a discussion of the present state of the subject and the prospects for the future.

For Tests No. 1 through 19, the mercury level was maintained at what is designated herein as Level A. Level A was that created by the placing of about 15.5 cc of Hg in the cylinder, whose capacity to contain 100% mercury was computed as 21.5 cc. This, depending on how one considered the displacement of the mercury during rotation, gave rise to a contact area on the disc (the minimum) of 6.11 or of 7.80 square inches.

The mercury level was reduced to Level B for Tests No. 20 and 23. This level provided an estimated minimum mercury contact of 3.63 square inches.

Tests No. 21 and 22 were conducted at Level C, which furnished a minimum mercury contact area of some 1.45 square inches.

As mentioned previously, maximum current ever passed through the brush was 48 amperes, which amount to 50 amperes per square inch through the carbon brushes. Actually, the carbon brushes functioned very well, but to prevent any loss of test time due to failure of the carbon brushes, old, of peculiar size and whose composition was unknown, it was decided to set this limit. On the other hand, 48 amperes represented a reasonable load on the rated 59-amperes generator which had just made a transcontinental trip; also the breaker was set for 50 amperes.

A graphical presentation of current density variation is given by Fig. 9, based upon the above calculations of

The first thing I noticed when I stepped out
of the car was the smell of the sea. It was
a salty, fresh scent that I had never before.
The air was cool and crisp, a perfect contrast
to the heat of the car. I took a deep breath,
savoring the moment. The sun was shining
brightly, and the water was a deep, vibrant
blue. I felt a sense of peace and tranquility
that I had never experienced before. The
sound of the waves crashing against the shore
was a soothing melody that filled my ears.
I walked along the beach, feeling the sand
beneath my feet. The sun was low in the
sky, casting a warm, golden glow over the
entire scene. I felt a sense of wonder and
awe at the beauty of the world around me.
The beach was empty, and I felt like I was
the only person in the world. I walked
until I reached the water's edge, where I
stood for a moment, looking out at the
horizon. The sun was setting, and the sky
was a mix of orange, red, and purple.
I felt a sense of peace and tranquility that
I had never experienced before. The sound
of the waves crashing against the shore was
a soothing melody that filled my ears. I
walked along the beach, feeling the sand
beneath my feet. The sun was low in the
sky, casting a warm, golden glow over the
entire scene. I felt a sense of wonder and
awe at the beauty of the world around me.

minimum mercury contact area.

For tests No. 1 through 18, the cylinder was the positive (+) terminal; for tests No. 19 through 23, the disc was the positive terminal.

For tests No. 1 through 18, the carbon brush pressure was the maximum (actual value not determined); for tests No. 19 through 23, the carbon brush pressure was the minimum (actual value not determined).

RESULTS

No. 4780SI
Colored Tabs
No. 4781SI
Clear Tabs

MADE IN U. S. A.

NATIONAL INSERTABLE-TAB INDEXES ENABLE YOU TO
MAKE YOUR OWN SUBJECT ARRANGEMENT, USING PLAIN
INSERTS ON WHICH TO WRITE YOUR OWN CAPTIONS.

DIAGNOSTIC

RESULTS

Of the 23 tests, the first four were excluded from consideration on the basis that they were conducted at speed levels below that of interest. The first four tests were intentionally so conducted in order to permit observation of the test device in operation as designed before the higher speeds were attempted.

The data taken as listed under the Procedure Section was put into tabular form; certain derived factors added; certain averages taken and included herein as Tables I through XV. Current densities both for the carbon and mercury were computed, as was the carbon brush drop. A curve of current densities, already mentioned, appears as Fig. 9. Also computed was the relative speed of the cylinder surface in contact with the mercury with respect to the disc surface in contact with the mercury and moving in the opposite direction. This amounted simply to the sum of the separate peripheral velocities of the two respective surfaces. Figures 10 and 11 show in convenient graphic form the relation between rpm and peripheral velocity as function of diameter.

It is important that the manner of taking the brush drops be noted. Due to the rather poor contact made by the carbon brushes and by the brass spring leaf pickoff's, these two voltages fluctuated through easily detectable ranges as much as 0.2 to 0.4 of a volt. Thus the data recorded in

Tables I through XV reflect the observer's opinion of the value the two meters were attempting to indicate, and may therefore be in error to some extent. This was not true of many readings, however, and in all cases readings were observed long enough (as long as several minutes in some cases) to reasonably establish the mean indication.

In addition to the tabular reduction of the recorded data, certain graphical plots were prepared.

Fig. 12 is a plot of the drop across the mercury brush as a function of contact speed for three different currents for Tests No. 5 through 19. Its source was Tables I through XII.

Fig. 13 shows the same information, plotted on a smaller scale, as Fig. 12, plus the addition of Tests No. 20 through 23, plus the addition of heat rise information on these 19 tests. The additional information was obtained from Tables XVI and XVII. The plotted temperature rise, Table XVII, was the average of the two thermometer indications.

Fig. 14 is a plot of the mercury brush drop as a function of brush current for several different relative speeds. Its source, as well, lies variously in Tables I through XV.

Finally, Fig. 15 is a plot (of Test No. 21 only) of the mercury brush drop vs. time at 10,350 rpm relative (107 f.p.s. relative). This was the greatest speed attained: for various reasons, to be pointed out, greater speeds with the test device in its present form were not possible. Fig. 15

also shows the temperature variation of both disc and cylinder throughout the test. This Test No. 21 was the most thoroughly conducted of all tests, it is believed, and for that reason it was plotted separately. In retrospect, all tests should have been similarly conducted, but as mentioned earlier, the experiment really only reached the point for good testing when it had to be stopped for want of time. Test No. 21 is tabulated in Table XIV.

DISCUSSION

A good understanding of the defects and shortcomings of the test device is a first requisite in evaluating the results obtained. These deficiencies have been raised variously throughout the report.

For the first series of tests; that is, No. 1 through No. 19, the mercury level was the greatest used. In turn, for these tests, current density was least. It was first thought such a volume of mercury would lead to best results, but this was not the case. As the higher rpm were approached three objectionable features became apparent.

The first to be noticed was the high heat generated on the rim of the cylinder due to nothing more than friction. This, in turn, led secondly to expansion of the cylinder and at 3000 rpm absolute, the combination of heat and centrifugal force was enough to permit a fine spray of mercury to be thrown out through the threaded joint by which the two pieces of the cylinder were joined. The canopy shielding the rotating parts proved essential here.

The third objection to the high level of mercury was again mechanical. The oppositely rotating disc seemed to "roll up" the mercury between it and the cylinder. This led to unbalance which at the higher rpm created heavy vibration in the device.

From the heat standpoint, there were two other defects. The walls of the cylinder were $1/4$ " thick; probably thicker than they need have been by perhaps as much as $3/16$ ". These thick walls, without cooling fins, simply could not radiate heat efficiently enough. Also, since an arbitrary maximum temperature on either thermometer had been established as 100°C , an unnecessary limitation was imposed by the fact the $5/16$ " shaft had to be provided with a $5/32$ " core to permit insertion of the thermometers. At the point where the cylinder was screwed on to its shaft, there were two or three threads which did not go fully into the cylinder. This combination of a drilled-out center and exposed exterior threads created a hot spot due to current flow through the very narrow cross-section at this point. It was thus always a question with just what share of the heat was the mercury to be credited. This hot spot is indicated as "B" in Fig. 2.

Another hot-spot problem arose where the pressed-paper seal raced on the disc shaft.

Accordingly, three steps were taken to remedy the above problems. To alleviate the hot-spot at the thin cross-section of the cylinder shaft, a bead of solder was laced about the shaft at "B" of Fig. 2. To reduce heat due to friction within the mercury, the mercury level was reduced (see Fig. 9). To reduce the hot-spot at the seal, it was removed and part of it filed away.

When the device was re-started, it was at once apparent too much of the seal had been removed, but it

coincidentally gave opportunity to note the nature of the turbulence in the mercury. It had been thought centrifugal force was holding the mercury smoothly away from the center and that the seal was not really needed. Actually, there must have been terrific turbulence in the mercury if the degree of leakage through the seal was any index. It was also interesting to note the leaking out the seal could be stopped by speeding up the cylinder. This led to a restoration of the seal and a further reduction of the mercury level.

Now, upon re-starting, improvement over initial operating conditions was clearly noted. It was possible now to run the device up to 10,350 rpm relative, and indications were higher peripheral velocities could be obtained.

There was some trouble with voltage pickoff across the mercury brush. At first it had been intended to take this voltage through the bearings. This was a futile proceeding; no voltage indication where voltage was known to be. It was clear after the situation presented itself that the bearing grease was acting as an insulator. The answer was to take the voltage off two brass spring leaf probes riding on the side of the brass slip rings. Even these gave fluctuating voltage readings, though great improvement was attained simply by smudging the pickoff race with carbon.

It was because of these pickoffs that ohmmeter readings were not taken seriously. Whereas some contact resistance at the probes would have little effect on the

100,000 ohms per volt voltmeter being used, they were thought possibly to show a good deal more resistance than would the mercury. Ohmic readings ran anywhere from 16 ohms to 60 ohms measured across the pickoff's during rotation; at standstill, readings were variously 2 to 5 ohms. The ohmmeter was used mainly to insure a closed circuit through the brush before loading it electrically, as otherwise the full supply voltage would have appeared across the 3-V voltmeter.

In this connection, one inadvertent open-circuit did develop across the mercury brush. Test No. 22 followed Test No. 21 very closely, the first being at 10,350 rpm relative; the second at 6,000 rpm relative. Obviously enough, mercury was thrown from the cylinder at 10,350 rpm almost to deplete it. At the end of Test No. 22 (do see Table XV) during which there was no leakage, when the current was dropped from 25 amperes to only 5 amperes, the brush voltage dropped from 0.35 volt to 0.05 volt and this voltage could be repeated by shutting the current on and off, 0 to 5 amps. Curious over this, speeds were increased toward 10,000 rpm again which immediately opened the circuit at the mercury brush. From this, it appeared that there does exist an optimum minimum mercury volume, or conversely, an optimum maximum current density. It should be obvious here that Fig. 9 is very probably in error concerning Tests No. 21 and 22. Time did not permit looking

into this interesting occurrence any further. It does appear such optimum should be sought and great pains taken to prevent any leaking so that good quantitative information could be obtained.

With this much background, it is now clear to the reader that any observations to be made concerning the experiment should be qualitative only, in spite of the rather formidable mass of data taken.

Fig. 12, a plot of mercury brush voltage drop vs. contact speed, would indicate that the drop increased both with contact speed and current density. However, it may actually be that the drop is independent of either current density or contact speed, and is rather dependent on heat only, since both increase in current density and in contact speed lead to heat generation. It is well known that resistance of metallic conductors increases with temperature. The drop being measured was not strictly across just the mercury. Actually, the drop was being measured across part of each brass slip ring, across about 4" of steel shaft of very narrow cross-section, and across the steel disc and cylinder, all of which became heated along with the mercury.

Fig. 13 seems to indicate a temperature effect rather than a speed or current density effect. Tests No. 20 through 23 were run after the remedial heat-reducing steps discussed earlier were taken. Fig. 13 shows a decrease in voltage drop across the mercury brush for the last four tests as compared to the previous fifteen. For the last four tests, current density was greater than during the previous fifteen and speeds were greater.

It is seen that the velocity of the reaction is not affected by the concentration of the reactants. It is also seen that the reaction is not affected by the presence of a catalyst. The reaction is therefore a zero-order reaction.

With this as a background, it is now clear to the reader that any observation to be made concerning the reaction should be qualitative only, in spite of the rather formidable mass of data shown.

Fig. 1, a plot of average pressure versus time, is shown. It is seen that the drop in pressure is not linear with time, as would be expected for a first-order reaction. However, it is actually found that the drop is independent of either current density or catalyst concentration and is rather dependent on time only, since both increase in current density and in catalyst concentration lead to a faster reaction. It is well known that resistance of catalysts increases with temperature. The drop being measured was not directly proportional to the current density, actually, the drop was being measured across part of each brass slip ring, across about 40 of about 100 turns of very narrow cross-section, and across the steel slip ring and cylinder, all of which become heated along with the catalyst. Fig. 2 shows a plot of the temperature effect versus time. It is seen that the drop in pressure is not linear with time, as would be expected for a first-order reaction. However, it is actually found that the drop is independent of either current density or catalyst concentration and is rather dependent on time only, since both increase in current density and in catalyst concentration lead to a faster reaction. It is well known that resistance of catalysts increases with temperature. The drop being measured was not directly proportional to the current density, actually, the drop was being measured across part of each brass slip ring, across about 40 of about 100 turns of very narrow cross-section, and across the steel slip ring and cylinder, all of which become heated along with the catalyst.

Fig. 14 would also appear to support the above opinion. In Fig. 14 the drop across the mercury brush is plotted against current. Here again it may be seen that by reducing the heat generated (Test No. 21), the voltage drop was less at 10,350 rpm than at 6,000 rpm for Test No. 14.

A comparison of Test No. 22 at 6,000 rpm, Table XV, with Test No. 25 at 10,350 rpm, Table XIV, both at about the same current density and both showing similar temperature rises, would appear to indicate the decrease in voltage drop of Test No. 22 was speed motivated.

A comparison of Test No. 22 at 6,000 rpm of high current density with Test No. 14, Table X, at low current density, would seem to show the decrease in voltage drop of Test No. 22 was current density motivated.

None of the effects on the voltage drop across the mercury brush were of great magnitude, however. The voltage drop varied from a minimum (excluding the point at 0.05 volt) of about 0.5 volt at 3,000 rpm relative to a minimum of about 0.7 volt at 10,350 rpm relative.

Although a comparison of the mercury brush against the carbon brush would not be fair in this test, an examination of the data sheets will show the carbon drop to be consistently higher. The carbon brush drop tabulated is that for two carbon brushes in series.

Though not under investigation, the carbon brushes did show some interesting (and well known) characteristics. It was observed that when current was reduced suddenly the

A comparison of Test No. 22 at 6,000 rpm of this engine
 with Test No. 14, Table 2, at low internal efficiency.
 would seem to show the decrease in voltage due to Test 22.
 The amount of this decrease is not indicated.

about 0.5 volt at 10,000 rpm relative to about 0.7 volt at 1,000 rpm relative to a solution of

[illegible]

carbon brush drop would decrease as suddenly to about one-quarter of its original value. Within a few minutes at the reduced current, the carbon voltage drop would build back to its original value. It was also easy to observe the fact that there was less drag of the carbon brushes on their slip rings when current was flowing than when running on open circuit. The carbon brush drop also increased as brush pressure decreased.

Pure mercury was used in this experiment. At no time did any of the leakage mercury appear to have oxidized or to show any other change in appearance. The possibility of a change in the mercury with age in the brush is not being overlooked; a life-test is indicated here. Also, the effect of the mercury on the container with time should be examined. In this connection the addition of a slight amount of titanium^u or zirconium to mercury is said to completely inhibit its attack on steel. Also, a better wetting of the steel surface by the mercury is claimed to be effected by the presence of a tiny amount of magnesium. These and other facts about mercury appear in Appendix B as excerpts from Ref. 3. Some of the physical properties of mercury are given in Table XVIII.

carbon black from your source as indicated above. The
one-quarter of the original value. The value of the
at the present moment, the value will be about half
back in its original value. It was also said to be
fact that there was a loss of the carbon black in the
the rings were removed and the rings were removed in
new spirit. The carbon black was also removed in
which present situation.

These matters are said to be extremely, as in the
did any of the former matter seem to be added or
to show any other change in appearance. The appearance of
a change in the matter was in the fact that it was
questioned: a little more is indicated here. The value
of the matter in the present with the value is reduced.
in this connection the addition of a small amount of
little or addition to matter is said to be extremely in-
crease its value on steel. Also, a better position of the
steel will be to the matter as stated to be added to
the presence of a tiny amount of material. There will then
facts about matter appear in the matter of the matter. The
fact. 2. Some of the objects of the matter of matter are
given in Table III.

CONCLUSIONS

The word "conclusion" carries with it too final a ring for this experiment as thus far conducted. Perhaps some opinion can be expressed.

1. A mercury brush is a satisfactory device electrically at sea level.
2. The voltage drop induced by current flow across a moving mercury-steel contact is independent of current density and speed of contact.

The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report. The organization of the data is the primary concern of the report.

1. The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report.

2. The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report.

3. The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report.

4. The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report.

5. The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report.

6. The word "organization" is used in the title of this report to indicate that the organization of the data is the primary concern of the report.

RECOMMENDATIONS

These recommendations could concern only those who might be interested in pursuing the project further along similar lines.

1. The "disc" should be fixed and only the "cylinder" rotate.

2. Some sort of variable-speed drive up to 12,000 rpm would be useful.

3. The cylinder diameter should be increased progressively to permit investigation up to an absolute maximum peripheral speed.

4. The use of the liquid conductor brush on an actual machine would serve to eliminate the carbon brushes.

5. Drive shaft size should be kept large enough to obviate heat generation due to current flow in it.

6. It would be desirable to build into the device some sort of plastic window to permit visual observation of the phenomena occurring.

7. The means of picking off the voltage drop across the brush should be improved.

8. The effect of varying the gap length shorted by the liquid conductor should be investigated.

9. The effect of varying the contact area (current density) needs further investigation.

CONCLUSIONS

These recommendations could be carried out in the following order:

1. The "stick" should be fixed and only the "ball" should be moved.

2. Some sort of vertical - wheel drive as in Fig. 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100.

3. The "ball" should be fixed and only the "stick" should be moved.

4. The use of the "stick" should be fixed and only the "ball" should be moved.

5. The use of the "ball" should be fixed and only the "stick" should be moved.

6. The use of the "stick" should be fixed and only the "ball" should be moved.

7. The use of the "ball" should be fixed and only the "stick" should be moved.

8. The use of the "stick" should be fixed and only the "ball" should be moved.

9. The use of the "ball" should be fixed and only the "stick" should be moved.

10. The use of the "stick" should be fixed and only the "ball" should be moved.

11. The use of the "ball" should be fixed and only the "stick" should be moved.

12. The use of the "stick" should be fixed and only the "ball" should be moved.

(Continued on next page)

10. The liquid conductor container should be seamless in the region where the fluid will circulate during rotation.

11. An effective seal against leakage about the "disc" shaft is an essential.

12. The test data to be taken should be given careful consideration and every test identically conducted.

13. A life-test of the device should be conducted after which a critical examination of the contact surfaces and the fluid conductor should be made.

10. The light sensor should be able to sense

light in the region where the light will directly impinge

rotation.

11. An effective test should be made about the "dead"

point in the rotation.

12. The test area to be taken should be given special

consideration and every test should be conducted.

13. A list of the device should be prepared

after which a critical evaluation of the system will

be made and the final evaluation should be made.

REFERENCES

1. A thesis by LT R. E. Morris, USN, listing the high-altitude carbon brush problems, U.S. Naval Postgraduate School, June 1952.
2. Noeggerath, J.S.: Acyclic (Homopolar) Dynamos, Proceedings of A.I.E.E., Vol. XXIV, January 1905, Page 19.
3. Liquid Metals Handbook, NavExos P-733, 1 June 1950, Atomic Energy Commission, Department of the Navy, Washington, D. C.

1. A study by J. H. D. Jones, 1955, "The Effect of the Hydro-
static Pressure on the Growth of the Fish, *Salmo gairdneri*,
Reared in Water of Different Salinities," *Journal of the
Royal Society of Medicine*, 48, 1-10.
2. A study by J. H. D. Jones, 1955, "The Effect of the Hydro-
static Pressure on the Growth of the Fish, *Salmo gairdneri*,
Reared in Water of Different Salinities," *Journal of the
Royal Society of Medicine*, 48, 1-10.



No. 4780SI
Colored Tabs
No. 4781SI
Clear Tabs

MADE IN U. S. A.

NATIONAL INSERTABLE-TAB INDEXES ENABLE YOU TO
MAKE YOUR OWN SUBJECT ARRANGEMENT, USING PLAIN
INSERTS ON WHICH TO WRITE YOUR OWN CAPTIONS.

TABLE I
RESULTS OF TEST NO. 5

Start Test No. 5 @ 1400; Stop @ 1430

RPM, disc.900

RPM, cylinder.600

Speed, relative, f.p.s. . 15

Ambient temp, °C 29

Date15 May 1952

Brush Current, Amperes	Carbon Current Density Amp/In ²	Mercury Current Density Amp/In ²	Total Brush Drop Volts	Carbon Brush Drop Volts	Mercury Brush Drop Volts	* Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp. Rise °C
4	4.26	.65	2.35	1.89	.46	5	7	8
8	8.52	1.31	2.75	2.31	.44	7	8	10
12	12.78	1.96	2.80	2.36	.44	9	9	12
16	17.04	2.52	2.90	2.40	.50	12	9	14
20	21.33	3.27	3.10	2.64	.46	14	13	17
24	25.56	3.93	3.10	2.58	.52	17	14	21
28	29.82	4.58	3.20	2.66	.54	19	17	25
32	34.08	5.24	3.30	2.73	.57	21	19	31
36	38.34	5.89	3.40	2.84	.56	22	22	36
40	42.66	6.55	3.45	2.85	.60	23	25	40
44	46.86	7.20	3.60	2.99	.61	24	29	44
48	51.15	7.85	3.80	3.17	.63	25	32	49
48	51.15	7.85	3.75	3.09	.66	30	#49	#69

*Approximated on basis of later timed tests.

#Temperature stabilized.

DATE OF YOUR DEATH IS . . .

000 1000 , 1000
 000 1000 , 1000
 00 1000 , 1000
 00 1000 , 1000
 000 1000 , 1000

TABLE II
RESULTS OF TEST NO. 6

Start Test No. 6 @ 1445; Stop @ 1515.

RPM, disc. 1300
RPM, cylinder. 700
Speed, relative, fps. . . 20
Ambient temp, °C 30
Date. 15 May 1952

Brush Current, Amperes	Carbon Current Density Amp/In ²	Mercury Current Density Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	* Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp. Rise °C
5	5.33	.82	2.35	2.03	.32	5	17	13
10	10.66	1.64	2.65	2.30	.35	8	17	13
15	16.00	2.46	2.80	2.46	.34	11	17	15
20	21.33	3.27	3.10	3.08	.32	14	18	20
25	26.66	4.09	3.15	2.80	.35	17	19	23
30	32.00	4.91	3.20	2.88	.32	19	21	26
35	37.33	5.73	3.20	2.82	.38	21	23	30
40	42.66	6.55	3.35	2.97	.38	23	25	33
45	48.00	7.36	3.45	3.05	.40	24	28	39
48	51.15	7.85	3.60	3.22	.38	25	31	44
48	51.15	7.85	3.80	3.36	.44	30	#45	#63

*Approximated on basis of later timed tests.

#Temperature stabilized.

2000 年 10 月 1 日

[illegible]

TABLE III
RESULTS OF TEST NO. 7

Start Test No. 7 @ 1530; Stop at 1550

RPM, disc.1300
RPM, cylinder. . . .1200
Speed, relative,
f.p.s.25.5
Ambient temp. °C . .30
Date.15 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp. Rise °C
5	5.33	.82	2.50	2.10	.40	1	15	13
10	10.66	1.64	2.90	2.44	.46	2	15	13
15	16.00	2.46	2.95	2.63	.32	3	16	15
20	21.33	3.27	2.95	2.62	.33	4	17	19
25	26.66	4.09	3.15	2.81	.34	5	19	23
30	32.00	4.91	3.25	2.89	.36	6	20	27
35	37.33	5.73	3.35	2.97	.38	7	23	30
40	42.66	6.55	3.60	3.20	.40	8	26	39
45	48.00	7.36	3.80	3.38	.42	12	32	47
48	51.15	7.85	3.95	3.31	.64	15	34	49
48	51.15	7.85	4.00	3.36	.64	20	#44	#61

*Approximated on basis of later timed tests.

#Temperature stabilized.

DATE OF SALE: 1997-07-10

OCEAN with city
 OCEAN weather (10)
 available, broad
 2.00 1.00
 OCEAN 1.00
 SURF 1.00

Year	Population	Area	Population Density	Area	Population Density	Area	Population Density	Area	Population Density
1900	1,000,000	100,000	10	100,000	10	100,000	10	100,000	10
1910	1,200,000	120,000	12	120,000	12	120,000	12	120,000	12
1920	1,400,000	140,000	14	140,000	14	140,000	14	140,000	14
1930	1,600,000	160,000	16	160,000	16	160,000	16	160,000	16
1940	1,800,000	180,000	18	180,000	18	180,000	18	180,000	18
1950	2,000,000	200,000	20	200,000	20	200,000	20	200,000	20
1960	2,200,000	220,000	22	220,000	22	220,000	22	220,000	22
1970	2,400,000	240,000	24	240,000	24	240,000	24	240,000	24
1980	2,600,000	260,000	26	260,000	26	260,000	26	260,000	26
1990	2,800,000	280,000	28	280,000	28	280,000	28	280,000	28
2000	3,000,000	300,000	30	300,000	30	300,000	30	300,000	30

...the
... ..

TABLE IV
RESULTS OF TEST NO. 8

Start Test No. 8 @ 1430; Stop @ 1510

RPM, disc. 1500
RPM, cylinder. 1500
Speed, relative, f.p.s. . . . 31
Ambient temp., °C. 27
Date. 16 May 1952

Brush Current Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	* Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp. Rise °C
5	5.33	.82	2.25	1.75	.50	13	25	27
10	10.66	1.64	2.90	2.37	.53	15	23	28
15	16.00	2.46	3.15	2.61	.54	17	23	28
20	21.33	3.27	3.30	2.72	.58	19	24	31
25	26.66	4.09	3.40	2.78	.62	21	26	33
30	32.00	4.91	3.60	2.97	.63	23	28	40
35	37.33	5.73	3.70	3.04	.66	25	31	44
40	42.66	6.55	3.80	3.12	.68	28	34	49
45	48.00	7.36	3.85	3.17	.68	30	38	55
48	51.15	7.85	4.00	3.30	.70	32	42	60
48	51.15	7.85	4.00	3.30	.70	40	#53	#73

*Approximated on basis of later timed tests.

#Temperature stabilized.

TABLE 1 Summary of Data

Source: Bureau of Economic Warfare, 1945

1. Total value of goods shipped to the United States from the Soviet Union, 1945.
 2. Total value of goods shipped to the United States from the Soviet Union, 1946.
 3. Total value of goods shipped to the United States from the Soviet Union, 1947.
 4. Total value of goods shipped to the United States from the Soviet Union, 1948.
 5. Total value of goods shipped to the United States from the Soviet Union, 1949.

Year	Value of Goods Shipped to the United States from the Soviet Union, 1945	Value of Goods Shipped to the United States from the Soviet Union, 1946	Value of Goods Shipped to the United States from the Soviet Union, 1947	Value of Goods Shipped to the United States from the Soviet Union, 1948	Value of Goods Shipped to the United States from the Soviet Union, 1949
1945	100.0	100.0	100.0	100.0	100.0
1946	100.0	100.0	100.0	100.0	100.0
1947	100.0	100.0	100.0	100.0	100.0
1948	100.0	100.0	100.0	100.0	100.0
1949	100.0	100.0	100.0	100.0	100.0

1. Total value of goods shipped to the United States from the Soviet Union, 1945.
 2. Total value of goods shipped to the United States from the Soviet Union, 1946.

TABLE V

RESULTS OF TEST NO. 9

Start Test No. 9 @ 1530; Stop @ 1550

RPM, disc.1800
 RPM, cylinder.1700
 Speed, relative, f.p.s. . . . 36
 Ambient temp, °C27
 Date.16 May 1952

Brush Current, Amperes	Carbon Current Density Amp/In ²	Mercury Current Density Amp/In ²	Total Brush Drop Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	* Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
5	5.33	.82	2.40	1.94	.46	1	23	20
10	10.66	1.64	2.90	2.36	.54	2	24	22
15	16.00	2.46	3.05	2.51	.54	3	25	25
20	21.33	3.27	3.25	2.65	.60	4	26	28
25	26.66	4.09	3.40	2.78	.62	5	29	34
30	32.00	4.91	3.55	2.92	.63	6	33	43
35	37.33	5.73	3.65	2.97	.68	7	35	47
40	42.66	6.55	3.80	3.12	.68	9	39	51
45	48.00	7.36	4.00	3.28	.72	11	43	57
48	51.15	7.85	4.00	3.28	.72	13	47	62
48	51.15	7.85	3.85	3.15	.70	20	#55	#73

*Approximated on basis of later timed tests.

#Temperature stabilized.

STATE OF TEXAS COUNTY OF DALLAS

Know all men by these presents, that I, the undersigned, do hereby certify that the following is a true and correct copy of the original as the same appears from the records of the County of Dallas, State of Texas, to-wit:

1890.
1891.
1892.
1893.
1894.
1895.
1896.
1897.
1898.
1899.
1900.

Page	Book	Page	Book	Page	Book	Page	Book	Page	Book
1	1	2	1	3	1	4	1	5	1
6	1	7	1	8	1	9	1	10	1
11	1	12	1	13	1	14	1	15	1
16	1	17	1	18	1	19	1	20	1
21	1	22	1	23	1	24	1	25	1
26	1	27	1	28	1	29	1	30	1
31	1	32	1	33	1	34	1	35	1
36	1	37	1	38	1	39	1	40	1
41	1	42	1	43	1	44	1	45	1
46	1	47	1	48	1	49	1	50	1
51	1	52	1	53	1	54	1	55	1
56	1	57	1	58	1	59	1	60	1
61	1	62	1	63	1	64	1	65	1
66	1	67	1	68	1	69	1	70	1
71	1	72	1	73	1	74	1	75	1
76	1	77	1	78	1	79	1	80	1
81	1	82	1	83	1	84	1	85	1
86	1	87	1	88	1	89	1	90	1
91	1	92	1	93	1	94	1	95	1
96	1	97	1	98	1	99	1	100	1

* Notarized on this day of the month of 1900.

Table VI
RESULTS OF TEST NO. 10

Start Test No. 10 @ 1030; stop @ 1051

RPM, disc. 2000
RPM, cylinder. 2000
Speed, relative, f.p.s. . . 41
Ambient temp., °C 27
Date. 19 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	* Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
5	5.33	.82	2.75	2.24	.51	1	23	20
10	10.66	1.64	3.15	2.62	.53	2	25	23
15	16.00	2.46	3.35	2.77	.58	3	26	26
20	21.33	3.27	3.45	2.87	.58	4	27	30
25	26.66	4.09	3.60	2.98	.62	5	29	35
30	32.00	4.91	3.65	3.01	.64	7	33	42
35	37.33	5.73	3.70	3.06	.64	9	36	46
40	42.66	6.55	3.90	3.20	.70	11	40	50
45	48.00	7.36	4.00	3.27	.73	13	43	56
48	51.15	7.85	4.00	3.27	.73	15	47	63
48	51.15	7.85	4.00	3.27	.73	21	#57	#73

*Approximated on basis of later timed tests.

#Temperature stabilized.

REPORT OF THE COMMISSIONER OF THE LAND OFFICE

MADE PUBLIC BY THE COMMISSIONER OF THE LAND OFFICE

1880.
1881.
1882.
1883.
1884.
1885.

Year	Area	Value	Cost	Profit	Loss	Net	Gross	Net
1880	100	100	100	100	100	100	100	100
1881	100	100	100	100	100	100	100	100
1882	100	100	100	100	100	100	100	100
1883	100	100	100	100	100	100	100	100
1884	100	100	100	100	100	100	100	100
1885	100	100	100	100	100	100	100	100
1886	100	100	100	100	100	100	100	100
1887	100	100	100	100	100	100	100	100
1888	100	100	100	100	100	100	100	100
1889	100	100	100	100	100	100	100	100
1890	100	100	100	100	100	100	100	100
1891	100	100	100	100	100	100	100	100
1892	100	100	100	100	100	100	100	100
1893	100	100	100	100	100	100	100	100
1894	100	100	100	100	100	100	100	100
1895	100	100	100	100	100	100	100	100
1896	100	100	100	100	100	100	100	100
1897	100	100	100	100	100	100	100	100
1898	100	100	100	100	100	100	100	100
1899	100	100	100	100	100	100	100	100
1900	100	100	100	100	100	100	100	100

* Approximate value of land in 1880.
* Approximate value of land in 1880.

TABLE VII

RESULTS OF TEST NO. 11

Start *Test No. 11 @ 1117; Stop @ 1142

RPM, disc. 2250
 RPM, cylinder. 2250
 Speed, relative, f.p.s 46.5
 Ambient temp., °C 27
 Date 19 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
5	5.33	.82	2.80	2.22	.58	1	27	22
10	10.66	1.64	3.20	2.60	.60	4	28	24
15	16.00	2.46	3.30	2.68	.62	5	29	26
20	21.33	3.27	3.35	2.72	.63	6	29	27
25	26.66	4.09	3.50	2.85	.65	8	31	32
30	32.00	4.91	3.65	2.97	.68	9	32	37
35	37.33	5.73	3.80	3.11	.69	11	33	42
40	42.66	6.55	3.80	3.09	.71	12	35	47
45	48.00	7.36	4.00	3.28	.72	13	37	52
48	51.15	7.85	4.00	3.27	.73	15	40	57
48	51.15	7.85	4.05	3.35	.70	25	#44	#69

*For Test No. 11 and subsequent tests, an 18" fan was directed on the cylinder from a distance of about 12". Estimate blast at 1" to 2" of water.

#Temperature stabilized.

Notes: 1. All tests were made at a rate of 1 in. per min.

2. The values in parentheses are the values for the material as received.
3. The values in parentheses are the values for the material as received.
4. The values in parentheses are the values for the material as received.

Specimen	Yield Point, lb/in. ²	Tensile Strength, lb/in. ²	Elongation, %	Reduction of Area, %	Impact, ft.-lb.	Charpy, ft.-lb.	Rockwell C	Brinell
1	30.0	45.0	10.0	40.0	10.0	10.0	40	100
2	30.0	45.0	10.0	40.0	10.0	10.0	40	100
3	30.0	45.0	10.0	40.0	10.0	10.0	40	100
4	30.0	45.0	10.0	40.0	10.0	10.0	40	100
5	30.0	45.0	10.0	40.0	10.0	10.0	40	100
6	30.0	45.0	10.0	40.0	10.0	10.0	40	100
7	30.0	45.0	10.0	40.0	10.0	10.0	40	100
8	30.0	45.0	10.0	40.0	10.0	10.0	40	100
9	30.0	45.0	10.0	40.0	10.0	10.0	40	100
10	30.0	45.0	10.0	40.0	10.0	10.0	40	100
11	30.0	45.0	10.0	40.0	10.0	10.0	40	100
12	30.0	45.0	10.0	40.0	10.0	10.0	40	100
13	30.0	45.0	10.0	40.0	10.0	10.0	40	100
14	30.0	45.0	10.0	40.0	10.0	10.0	40	100
15	30.0	45.0	10.0	40.0	10.0	10.0	40	100
16	30.0	45.0	10.0	40.0	10.0	10.0	40	100
17	30.0	45.0	10.0	40.0	10.0	10.0	40	100
18	30.0	45.0	10.0	40.0	10.0	10.0	40	100
19	30.0	45.0	10.0	40.0	10.0	10.0	40	100
20	30.0	45.0	10.0	40.0	10.0	10.0	40	100

*The tests were made at a rate of 1 in. per min. and the values are the average of three tests.

†The values are the average of three tests.

TABLE VIII

RESULTS OF TEST NO. 12

Start Test No. 12 @ 1155; Stop @ 1218

RPM, disc.2500
 RPM, cylinder.2500
 Speed, relative, f.p.s 51
 Ambient temp., °C 27
 Date.19 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
5	5.33	.82	2.75	2.16	.59	1	33	24
10	10.66	1.64	3.00	2.40	.60	2	34	24
15	16.00	2.46	3.10	2.48	.62	3	35	26
20	21.33	3.27	3.15	2.52	.63	5	36	29
25	26.66	4.09	3.20	2.55	.65	7	38	31
30	32.00	4.91	3.30	2.62	.68	9	39	36
35	37.33	5.73	3.75	3.05	.70	10	40	40
40	42.66	6.55	3.85	3.15	.70	12	42	46
45	48.00	7.36	4.00	3.28	.72	14	43	53
48	51.15	7.85	4.10	3.36	.74	15	45	58
48	51.15	7.85	4.15	3.47	.68	23	#49	#72

#Temperature stabilized.

0000 0000 0000
 0000 0000 0000
 0000 0000 0000
 0000 0000 0000
 0000 0000 0000

Year	Month	Day	Time	Location	Event	Remarks	Signature	Witness
1900	Jan	1	10:00	St. Paul	Meeting	First meeting of the year.	J. W. Smith	W. H. Jones
1900	Jan	15	10:00	St. Paul	Meeting	Second meeting of the year.	J. W. Smith	W. H. Jones
1900	Feb	1	10:00	St. Paul	Meeting	Third meeting of the year.	J. W. Smith	W. H. Jones
1900	Feb	15	10:00	St. Paul	Meeting	Fourth meeting of the year.	J. W. Smith	W. H. Jones
1900	Mar	1	10:00	St. Paul	Meeting	Fifth meeting of the year.	J. W. Smith	W. H. Jones
1900	Mar	15	10:00	St. Paul	Meeting	Sixth meeting of the year.	J. W. Smith	W. H. Jones
1900	Apr	1	10:00	St. Paul	Meeting	Seventh meeting of the year.	J. W. Smith	W. H. Jones
1900	Apr	15	10:00	St. Paul	Meeting	Eighth meeting of the year.	J. W. Smith	W. H. Jones
1900	May	1	10:00	St. Paul	Meeting	Ninth meeting of the year.	J. W. Smith	W. H. Jones
1900	May	15	10:00	St. Paul	Meeting	Tenth meeting of the year.	J. W. Smith	W. H. Jones

• *Forêt de la région de la forêt*

TABLE IX

RESULTS OF TEST NO. 13

Start Test No. 13 @ 1425; stop @ 1447

RPM, disc. 2750
 RPM, cylinder. 2750
 Speed, relative, f.p.s . . . 57
 Ambient temp., °C. 27
 Date. 19 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
5	5.33	.82	2.30	1.75	.55	1	36	20
10	10.66	1.64	2.55	1.95	.60	2	36	22
15	16.00	2.46	2.90	2.26	.64	4	36	26
20	21.33	3.27	3.20	2.52	.68	5	36	28
25	26.66	4.09	3.40	2.70	.70	6	38	31
30	32.00	4.91	3.45	2.75	.70	9	41	38
35	37.33	5.73	3.65	2.93	.72	10	42	41
40	42.66	6.55	3.70	2.97	.73	12	43	45
45	48.00	7.36	3.85	3.10	.75	13	45	51
48	51.15	7.85	3.90	3.13	.77	15	47	56
48	51.15	7.85	4.15	3.39	.76	22	#52	#68

#Temperature stabilized.

TABLE I

SUMMARY OF DATA FOR 1978

Sheet No. 1 of 10

Date: 10/10/78
 Author: J. A. Smith
 Title: Summary of Data for 1978

Year	Month	Day	Time	Location	Activity	Remarks
1978	Jan	1	08:00	Field	Survey	Clear
1978	Jan	2	09:00	Field	Survey	Clear
1978	Jan	3	10:00	Field	Survey	Clear
1978	Jan	4	11:00	Field	Survey	Clear
1978	Jan	5	12:00	Field	Survey	Clear
1978	Jan	6	13:00	Field	Survey	Clear
1978	Jan	7	14:00	Field	Survey	Clear
1978	Jan	8	15:00	Field	Survey	Clear
1978	Jan	9	16:00	Field	Survey	Clear
1978	Jan	10	17:00	Field	Survey	Clear
1978	Jan	11	18:00	Field	Survey	Clear
1978	Jan	12	19:00	Field	Survey	Clear
1978	Jan	13	20:00	Field	Survey	Clear
1978	Jan	14	21:00	Field	Survey	Clear
1978	Jan	15	22:00	Field	Survey	Clear
1978	Jan	16	23:00	Field	Survey	Clear
1978	Jan	17	00:00	Field	Survey	Clear
1978	Jan	18	01:00	Field	Survey	Clear
1978	Jan	19	02:00	Field	Survey	Clear
1978	Jan	20	03:00	Field	Survey	Clear
1978	Jan	21	04:00	Field	Survey	Clear
1978	Jan	22	05:00	Field	Survey	Clear
1978	Jan	23	06:00	Field	Survey	Clear
1978	Jan	24	07:00	Field	Survey	Clear
1978	Jan	25	08:00	Field	Survey	Clear
1978	Jan	26	09:00	Field	Survey	Clear
1978	Jan	27	10:00	Field	Survey	Clear
1978	Jan	28	11:00	Field	Survey	Clear
1978	Jan	29	12:00	Field	Survey	Clear
1978	Jan	30	13:00	Field	Survey	Clear
1978	Jan	31	14:00	Field	Survey	Clear

Continued on next sheet

TABLE X

RESULTS OF TEST NO. 14

Start Test No. 14 @ 1524; Stop @ 1551

RPM, disc. 3000
 RPM, cylinder. 3000
 Speed, relative, f.p.s 62
 Ambient temp., °C. 30
 Date. 19 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
5	5.33	.82	2.80	2.23	.57	1	48	15
5	5.33	.82	2.90	2.27	.63	9	45	20
10	10.66	1.64	3.15	2.52	.65	10	45	22
15	16.00	2.46	3.25	2.60	.68	12	46	23
20	21.33	3.27	3.50	2.82	.70	14	47	25
25	26.66	4.09	3.80	3.10	.72	16	48	33
30	32.00	4.91	3.90	3.18	.73	17	49	37
35	37.33	5.73	4.00	3.27	.74	18	50	40
40	42.66	6.55	4.20	3.46	.77	20	51	45
45	48.00	7.36	4.40	3.63	.78	21	53	50
48	51.15	7.85	4.50	3.72	.77	22	55	57
48	51.15	7.85	4.45	3.68		27	#58	#66

#Temperature stabilized.

TABLE XI

RESULTS OF TESTS NO. 15 & 16

Start Test No. 15 @ 1600; Stop @ 1611

RPM, disc. 3250
 RPM, cylinder. 3250
 Speed, relative, f.p.s. . . . 67
 Ambient temp., °C. 30
 Date. 19 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
48	51.15	7.85	4.30	3.55	.75	3	#64	54
48	51.15	7.85	4.50	3.75	.75	9	#67	64
48	51.15	7.85	4.50	3.75	.75	11	#70	66

Start Test No. 16 @ 1020; Stop @ 1032

RPM, disc. 3500
 rpm, cylinder. 3500
 Speed, relative, f.p.s. . . . 72
 Ambient temp, °C 25
 Date. 21 May 1952

48	51.15	7.85	4.30	3.55	.75	6	57	61
48	51.15	7.85	4.30	3.55	.75	7	60	65
48	51.15	7.85	4.45	3.69	.76	8	62	69
48	51.15	7.85	4.40	3.63	.77	9	64	70
48	51.15	7.85	4.25	3.47	.78	10	66	71
48	51.15	7.85	4.30	3.52	.78	11	67	72
48	51.15	7.85	4.40	3.62	.78	12	69	73

#Suspect this excessive rise due to binding seal.

Percentage of total population in each age group

Age group 0-14 years; 15-64 years; 65 years and over

Male, 1950
Female, 1950
Male, 1960
Female, 1960
Male, 1970
Female, 1970

Age group	Male, 1950	Female, 1950	Male, 1960	Female, 1960	Male, 1970	Female, 1970
0-14 years	21.1	21.1	21.1	21.1	21.1	21.1
15-64 years	68.2	68.2	68.2	68.2	68.2	68.2
65 years and over	10.7	10.7	10.7	10.7	10.7	10.7

Age group 0-14 years; 15-64 years; 65 years and over

Male, 1950
Female, 1950
Male, 1960
Female, 1960
Male, 1970
Female, 1970

0-14 years	21.1	21.1	21.1	21.1	21.1	21.1
15-64 years	68.2	68.2	68.2	68.2	68.2	68.2
65 years and over	10.7	10.7	10.7	10.7	10.7	10.7
0-14 years	21.1	21.1	21.1	21.1	21.1	21.1
15-64 years	68.2	68.2	68.2	68.2	68.2	68.2
65 years and over	10.7	10.7	10.7	10.7	10.7	10.7
0-14 years	21.1	21.1	21.1	21.1	21.1	21.1
15-64 years	68.2	68.2	68.2	68.2	68.2	68.2
65 years and over	10.7	10.7	10.7	10.7	10.7	10.7

TABLE XII

RESULTS OF TESTS NO. 17, 18 & 19

Brush Current, Amperes	Carbon Current Density Amp/In ²	Mercury Current Density Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
------------------------------	---	--	----------------------------------	-----------------------------------	------------------------------------	-----------------------------	----------------------------	--------------------------------

Test No. 17

RPM, disc. 3750
 RPM, cylinder. 3750
 Speed, relative, f.p.s. . 77.5
 Ambient temp., °C. . . . 25
 Date. 21 May 1952

48	51.15	7.85	4.40	3.65	.75	*10	#57	43
1	1.07	.16	--	--	.50	1	---	--

Test No. 18¹

RPM, disc. 1500
 RPM, cylinder. 1500
 Speed, relative, f.p.s. . 31
 Ambient temp., °C. . . . 25
 Date. 21 May 1952

48	51.15	7.85	4.00	3.50	.50	*10	#47	25
----	-------	------	------	------	-----	-----	-----	----

²Test No. 19

RPM, disc. 4000
 RPM, cylinder. 4000
 Speed, relative, f.p.s. . 83
 Ambient temp., °C. . . . 30
 Date. 23 May 1952

48	51.15	7.85	5.00	4.22	.78	5	#70	60
1	1.07	.16	----	----	.50	1	---	--

¹Continuation Test No. 17 wherein RPM reduced abruptly.

²Reversed polarity; made disc (+); also reduced carbon brush pressure to minimum.

*Estimated

#Due to binding seal.

OF THE

Year	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

VI. 21. 1905

Item	Quantity	Unit Price	Total
1.00	1.00	1.00	1.00
2.00	2.00	2.00	2.00
3.00	3.00	3.00	3.00
4.00	4.00	4.00	4.00
5.00	5.00	5.00	5.00
6.00	6.00	6.00	6.00
7.00	7.00	7.00	7.00
8.00	8.00	8.00	8.00
9.00	9.00	9.00	9.00
10.00	10.00	10.00	10.00
11.00	11.00	11.00	11.00
12.00	12.00	12.00	12.00
13.00	13.00	13.00	13.00
14.00	14.00	14.00	14.00
15.00	15.00	15.00	15.00
16.00	16.00	16.00	16.00
17.00	17.00	17.00	17.00
18.00	18.00	18.00	18.00
19.00	19.00	19.00	19.00
20.00	20.00	20.00	20.00
21.00	21.00	21.00	21.00
22.00	22.00	22.00	22.00
23.00	23.00	23.00	23.00
24.00	24.00	24.00	24.00
25.00	25.00	25.00	25.00
26.00	26.00	26.00	26.00
27.00	27.00	27.00	27.00
28.00	28.00	28.00	28.00
29.00	29.00	29.00	29.00
30.00	30.00	30.00	30.00
31.00	31.00	31.00	31.00
32.00	32.00	32.00	32.00
33.00	33.00	33.00	33.00
34.00	34.00	34.00	34.00
35.00	35.00	35.00	35.00
36.00	36.00	36.00	36.00
37.00	37.00	37.00	37.00
38.00	38.00	38.00	38.00
39.00	39.00	39.00	39.00
40.00	40.00	40.00	40.00
41.00	41.00	41.00	41.00
42.00	42.00	42.00	42.00
43.00	43.00	43.00	43.00
44.00	44.00	44.00	44.00
45.00	45.00	45.00	45.00
46.00	46.00	46.00	46.00
47.00	47.00	47.00	47.00
48.00	48.00	48.00	48.00
49.00	49.00	49.00	49.00
50.00	50.00	50.00	50.00
51.00	51.00	51.00	51.00
52.00	52.00	52.00	52.00
53.00	53.00	53.00	53.00
54.00	54.00	54.00	54.00
55.00	55.00	55.00	55.00
56.00	56.00	56.00	56.00
57.00	57.00	57.00	57.00
58.00	58.00	58.00	58.00
59.00	59.00	59.00	59.00
60.00	60.00	60.00	60.00
61.00	61.00	61.00	61.00
62.00	62.00	62.00	62.00
63.00	63.00	63.00	63.00
64.00	64.00	64.00	64.00
65.00	65.00	65.00	65.00
66.00	66.00	66.00	66.00
67.00	67.00	67.00	67.00
68.00	68.00	68.00	68.00
69.00	69.00	69.00	69.00
70.00	70.00	70.00	70.00
71.00	71.00	71.00	71.00
72.00	72.00	72.00	72.00
73.00	73.00	73.00	73.00
74.00	74.00	74.00	74.00
75.00	75.00	75.00	75.00
76.00	76.00	76.00	76.00
77.00	77.00	77.00	77.00
78.00	78.00	78.00	78.00
79.00	79.00	79.00	79.00
80.00	80.00	80.00	80.00

ВГ. О. 1. 1. 1.

[illegible]

St. John's

Rate	Interest exp.	Sum. relative	Sum. relative	Sum. relative
100	100	100	100	100
90	90	90	90	90
80	80	80	80	80
70	70	70	70	70
60	60	60	60	60
50	50	50	50	50
40	40	40	40	40
30	30	30	30	30
20	20	20	20	20
10	10	10	10	10
0	0	0	0	0

1. The above described work was done by the following persons:

[illegible]

* Low values of

TABLE XIII

RESULTS OF TEST NO. 20

Start Test No. 20 @ 1120; stop @ 1230

RPM, disc. 4000
 RPM, cylinder. 4000
 Speed, relative, f.p.s. . . 83
 Ambient temp., °C. 25
 Date. 26 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Brush Drop, Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
48	51.15	13.20	5.60	5.00	.60	14	57	63
			5.65	5.03	.62	15	59	63
			5.65	5.03	.62	16	60	62
			5.60	4.98	.62	18	60	65
			5.60	4.92	.68	21	60	66
			5.60	4.88	.72	24	60	67
			5.65	4.95	.70	26	60	68
			5.50	4.78	.72	29	60	70
			5.40	4.80	.60	30	59	70
			5.40	4.80	.60	31	59	70
			5.60	4.92	.68	33	57	70
			5.40	4.76	.64	39	58	72
			5.25	4.61	.64	41	57	71
			5.20	4.42	.78	43	57	71
			5.40	4.80	.60	45	57	71
48	51.15	13.20	5.50	4.86	.64	46	57	71
5	5.33	1.38	2.50	2.12	.38	47	53	67
			3.20	2.74	.46	49	47	52
			3.20	2.70	.50	51	42	40
			3.40	2.95	.45	53	39	33
			3.40	2.97	.43	56	37	29
			3.60	3.10	.50	58	37	27
			3.50	3.00	.50	60	38	26
5	5.33	1.38	3.45	2.95	.50	63	38	26
0	0	0	0	0	0	66	39	24
0	0	0	0	0	0	70	38	24

STATE OF TEXAS: 1900

1900.
1901.
1902.
1903.
1904.

Year	Property	Excise	License	Transfer	Other	Total	Per cent	Per cent
1900	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1901	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1902	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1903	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1904	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1905	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1906	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1907	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1908	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1909	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1910	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1911	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1912	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1913	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1914	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1915	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1916	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1917	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1918	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1919	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1920	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1921	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1922	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1923	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1924	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1925	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1926	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1927	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1928	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1929	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00
1930	100.00	100.00	100.00	100.00	100.00	500.00	100.00	100.00

RESULT OF TEST NO. 21

Start Test No. 21 @ 1325; Stop @ 1425

RPM, disc.5125
RPM, cylinder.5225
Speed, relative, f.p.s.107
Ambient temp., °C.	25
Date.26 May 1952

Brush Current Amperes,	Carbon Current Density, Amp/In ²	Mercury Current Density Amp/In ²	Total Brush Drop Volts	Carbon Brush Drop, Volts	Mercury Brush Drop, Volts	Elapsed Time, Minutes	Disc Temp. Rise °C	Cylinder Temp. Rise °C
0	0	0	0	0	0	5	42	15
						8	49	16
						10	38	16
						11	49	16
0	0	0	0	0	0	12	49	16
5	5.33	3.45	4.30	3.82	.48	13	49	19
5	5.33	3.45	4.40	3.92	.48	16	50	19
25	26.66	17.20	5.25	4.59	.66	17	52	25
			5.25	4.63	.62	19	54	32
			5.35	4.73	.62	21	55	37
			5.40	4.78	.62	23	54	38
			5.40	4.79	.61	25	54	40
			5.50	4.86	.64	28	54	41
			5.50	4.82	.68	30	54	42
			5.50	4.80	.70	33	53	43
			5.50	4.80	.70	33	53	43
25	26.66	17.20	5.50	4.83	.67	35	52	43
48	51.15	33.10	6.25	5.52	.73	36	55	47
48	51.15	33.10	6.05	5.32	.73	37	58	53
48	51.15	33.10	6.05	5.34	.71	38	59	59
48	51.15	33.10	6.00	5.30	.70	39	61	61
48	51.15	33.10	5.80	5.12	.68	40	62	66
48	51.15	33.10	5.85	5.15	.70	42	62	68
48	51.15	33.10	5.80	5.13	.67	43	62	69
48	51.15	33.10	5.80	5.20	.60	45	62	71
48	51.15	33.10	6.00	5.42	.58	47	62	72
48	51.15	33.10	6.00	5.40	.60	50	63	73
25	26.66	17.20	5.30	4.70	.60	51	61	70
25	26.66	17.20	5.50	4.87	.63	52	58	69
25	26.66	17.20	5.60	5.05	.55	53	58	60
5	5.33	3.45	3.95	3.43	.52	54	55	53
5	5.33	3.45	4.30	3.80	.50	56	53	45
5	5.33	3.45	4.65	4.00	.65	57	53	40
0	0	0	0	0	0	58	52	35
0	0	0	0	0	0	60	52	33

700

.

TABLE XV
RESULTS OF TESTS NO. ²²23, 23

Started Test No. 22 @ 1433; stop @ 1453

RPM, disc. 3000
RPM, cylinder. 3000
Speed, relative, f.p.s. . . 62
Ambient temp., °C. 25
Date. 26 May 1952

Brush Current, Amperes	Carbon Current Density, Amp/In ²	Mercury Current Density, Amp/In ²	Total Drop, Volts	Brush Drop Volts	Carbon Brush Drop Volts	Mercury Brush Drop Volts	Elapsed Time Minutes	Disc Temp Rise °C	Cylinder Temp Rise °C
		①							
48	51.15	33.10	5.60	5.25	.35	1	37	30	
48	51.15	33.10	4.50	4.18	.32	3	37	30	
48	51.15	33.10	4.60	4.20	.40	10	40	63	
48	51.15	33.10	5.50	5.12	.38	13	43	67	
25	26.66	17.20	----	----	.26	15	40	65	
25	26.66	17.20	4.50	4.15	.35	19	40	50	
5	5.33	3.45	2.70	2.65	#.05	20	--	--	

① Density probably much greater, as open-ckt developed shortly after Test 22.

Started Test No. 23 @ 1542; Stop @ 1606
Date, RPM, Ambient Same as Test No. 22

48	51.15	13.20	5.40	4.80	.60	1	25	48
			5.40	4.70	.70	4	33	53
			5.70	5.00	.70	6	35	58
			5.50	4.80	.70	8	37	61
			5.40	4.70	.70	10	39	62
			5.40	4.70	.70	12	40	63
48	51.15	13.20	5.50	4.80	.70	14	40	63
48	51.15	13.20	----	----	---	18	40	*--
5	5.33	1.38	3.00	2.40	.60	20	35	--
5	5.33	1.38	3.10	2.55	.55	22	28	--
5	5.33	1.38	3.40	2.85	.55	24	23	--

#This low reading no mistake; current was varied 0 to 50 and reading repeated.

*At this point, cylinder thermometer vibrated out of shaft and was bent.

[illegible]

0000 2876
 0000 2876
 0000 2876
 0000 2876
 0000 2876
 0000 2876

[illegible][illegible]

SUMMARY OF TESTS No. 20, 21, 22 & 23

TABLE XVI

Brush Current Amps.	Hg Current Density Amp/In ²	Rel. Spd. F.P.S.	Hg Volt Drop	Test Number
48	13.2	83	.66	20
5	1.38	83	.48	20
5	3.45	107	.52	21
25	17.2	107	.63	21
48	33.1	107	.67	21
48	33.1	62	.36	22
25	17.2	62	.30	22
5	3.45	62	.05	22
48	13.2	62	.69	23
5	1.38	62	.57	23

NOTE: Column 4 is an average over a "steady-state" period.

Year	1900	1901	1902	1903	1904
1900	100	100	100	100	100
1901	100	100	100	100	100
1902	100	100	100	100	100
1903	100	100	100	100	100
1904	100	100	100	100	100
1905	100	100	100	100	100
1906	100	100	100	100	100
1907	100	100	100	100	100
1908	100	100	100	100	100
1909	100	100	100	100	100
1910	100	100	100	100	100

1. The first step is to identify the problem. This involves understanding the situation and the goals that need to be achieved.

TABLE XVII

TEMPERATURE RISE SUMMARY OF ALL TESTS

Brush Curr. Amps.	Rel. Spd. F.P.S.	Aver. Temp. Rdgs. °C	Test No.	Brush Curr. Amps.	Rel. Spd. F.P.S.	Aver. Temp. Rdgs. °C	Test No.	Brush Curr. Amps.	Rel. Spd. FPS	Aver. Temp. Rdgs. °C	Test No.
5	20	15	6	5	46.5	25	11	5	83	32	20
25	20	21	6	25		32		48		64	
48	20	54	6	48		56		0		31	
5	25.5	14	7	5	51	28	12	0	107	32	21
25	25.5	21	7	25		35		5		34	
48	25.5	53	7	48		60		25		48	
								48		68	
5	31	26	8	5	57	28	13				
25		30	8	25		35		48	62	52	23
48		63	8	48		60					
5	36	21	9	5	62	32	14				
25		32		25		40					
48		64		48		62					
5	41	22	10	48	67	68	15				
25		32									
48		65		48	72	71	16				

Summary of the Year

Year	Month	Day	Time	Location	Event	Remarks
1900	Jan	1	10:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	2	11:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	3	12:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	4	13:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	5	14:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	6	15:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	7	16:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	8	17:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	9	18:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	10	19:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	11	20:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	12	21:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	13	22:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	14	23:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	15	24:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	16	25:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	17	26:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	18	27:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	19	28:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	20	29:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	21	30:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	22	31:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	23	32:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	24	33:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	25	34:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	26	35:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	27	36:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	28	37:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	29	38:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	30	39:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.
1900	Jan	31	40:00	City Hall	Meeting	Regular meeting of the Board of Aldermen.

TABLE XVIII
SOME PHYSICAL PROPERTIES
OF
MERCURY, IRON, COPPER

	<u>Hg.</u>	<u>Fe</u>	<u>Cu</u>
Atomic Weight	200.61	55.84	63.57
Density, gm. per cc.	13.546	7.87	8.89
Melting Point, °C	-38.87	1535	1083
Latent Heat of Fusion, g-Cal per g.	2.776	65	49.3
Boiling Point, °C	356.9	3200	2300
Latent Heat of Vaporization, g-cal per g.	71	1110	1756
Specific heat, Btu per lb.	.0333	.1075	.0928
Thermal Coeff. of Linear Expansion, x 10 ⁴ per °C	#	.119	.162
Thermal Cond., g-cal/sec/ cm ² /°C/cm	.0148	.18	.918
Electrical Resistivity, ohm cm cube	95.783	9.8	1.724
Temp Coeff of Resistivity	.00089	.0065	.00393

$$\# \frac{1}{v} \frac{dv}{dt} = 182 \times 10^{-6} @ 20^{\circ}\text{C}$$

$$\frac{dC}{dt} = -C \Gamma + C \beta \Gamma = \frac{C}{\beta} \left(\frac{\Gamma}{\beta} - \Gamma \right)$$



No. 4730SI
Colored Tabs
No. 4781SI
Clear Tabs

MADE IN U. S. A.

NATIONAL INSERTABLE-TAB INDEXES ENABLE YOU TO
MAKE YOUR OWN SUBJECT ARRANGEMENT, USING PLAIN
INSERTS ON WHICH TO WRITE YOUR OWN CAPTIONS.




Fig. 2. Photograph of test device.
Mercury is contained within
cylinder appearing in center.





Fig. 3. Front view of complete test apparatus.

FIG. 4

CALIBRATION CURVE
WESTON DC AMMETER
MODEL 45
SER. 59320



SCALE INDICATION, AMPERES

82.50, 135

CORRECTION

IN

VOLTS

FIG. 5
CALIBRATION CURVE
GENERAL ELECTRIC DC VOLT-METER
SER. 1112214

SCALE INDICATION VOLTS

SER. 1112214

3.0

2.8

2.6

2.4

2.2

2.0

1.8

1.6

1.4

1.2

1.0

.8

.6

.4

.2

0

0.01

0.02

0.03

0.04

0.05

0.06

0.07

0.08

0.09


0.10

0.11

0.12

0.13

FIG. 6
 CALIBRATION CURVE
 WESTINGHOUSE DC VOLTMETER
 SFR. 2357120
 0-10V SCALE



22 May 1952




Fig. 7. Left side view of apparatus.

Item
445





Fig. 8. Right side view of apparatus.


1


1


1


1















No. 4780SI
Colored Tabs
No. 4781SI
Clear Tabs

MADE IN U. S. A.

NATIONAL INSERTABLE-TAB INDEXES ENABLE YOU TO
MAKE YOUR OWN SUBJECT ARRANGEMENT, USING PLAIN
INSERTS ON WHICH TO WRITE YOUR OWN CAPTIONS.

10. 10. 1942

... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..

... ..
... ..
... ..

11. 10. 1942

APPENDIX A
LABORATORY LOG

... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..

12. 10. 1942

... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..

13. 10. 1942

... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..

22 APRIL 1952

Finally got down to work on thesis project at about 1415 p.m. Disassembled, cleaned and oiled. Fitted the carbon brushes to the brass slip rings. Required the help of Joe Octavek to open the cylinder in order that preservative oil could be cleaned out. Noted DC motors are shunt wound. Will have to exercise care that field doesn't open inadvertently.

For power will have to start up synchronous motor, DC generator set.

23 APRIL 1952

Cleaned oil out of conducting cylinder. Re-aligned and tightened entire mechanism. Mounted 2 armature slide-wire rheostats and 2 field slide-wire rheostats. Next plan to connect and test DC motors; be sure to uncouple v-belts. In testing for grounds, noted one v-belt shows less than infinite (500k) resistance. Re-check on 7 May showed infinite R both belts.

24 April 1952

Installed terminal lugs, connected motors. Started up AC-DC set and tested motors. Both run satisfactorily. Next plan to test rotary brush assembly for alignment and heat (temp.) rise.

25 APRIL 1952

Started the mechanism on slowest possible speed (motors on smallest pulleys) and noted temperature rises. Cylinder end stabilized at about 400-500 C, whereas disc end tended

to overheat (600-800°C). After a run-in of 30-40 minutes, disc end steadied at about 600°C. Next set motors on largest pulleys. Without extreme care in speed control, it was possible to rapidly and easily overheat the disc end. Trouble was at mercury seal, a pressed paper sleeve (journal) bearing on the disc shaft (and rotating with the cylinder). Temperature of disc end went as high as 1600°C; cylinder end steady at about 500°C. Permitted speeds such that disc end ran at about 1000-1200°C for 30-40 minutes. Noted small amount bearing grease on paper seal ^{was} of great help. Secured device, packed small quantity grease about paper seal in hope sufficient absorption would take place to permit cooler running. Necessary that device run cool in order to avoid danger of flashing mercury into vapor. To this extent, must remember to provide a ventilating blower once mercury is placed in cylinder.

30 APRIL 1952

Started device. Temperatures both ends steady at about 450-500°C., even at relative speed of 12,000 rpm. Connected and adjusted two strobotacs. Connected adjustable load resistor bank (1-72 amps) to provide current control for rotating brush. Connected ammeter and voltmeter to record current through brush and drops across carbon and Hg together and across Hg alone.

To provide for maximum control of speed and current, started up another M-G set. One set provided voltage for driving motors; other set providing voltage for load

resistor bank. In this way, have two speed controls: (1) field rheostat on DC generator; (2) armature and field rheostats in DC motors. Also then have two current controls: (1) field rheostat on second DC generator; (2) rotary switch on load bank (parallel connected).

Load bank is good for 72 amps. (Go to 48 amps.)

Started up both M-G sets; brought motors up to speed (about 4,000 each rpm); shorted out rotating brush (since as yet no mercury in it); and put about 6 amps through carbon brush assembly. Noted voltmeters as connected to read from pedestal-to-pedestal would give no readings. Investigation showed grease on bearings sufficient to act as insulator. In probing with ohmmeter, noted resistance of rotating brush had dropped from about 500 k Ω (prior to greasing seal) to 26 k Ω . This of no consequence, particularly since mercury when added will drop resistance to very low value, anyway.

With the 6 amps (about) through the carbon brushes with the cylinder and disc shorted out, noted about a 4-volt drop across the carbon brushes. This would be the drop across all four brush sets in series.

At this point there was a main power failure on the station. Secured for the day. It does appear there will be a problem in determining the drop across the mercury brush alone.

During actual conduct of test with mercury, carbon, brush drop will be that of only two brushes.

resistor bank. In this case, have two series resistors (1)

field resistor in the resistor; (2) resistor and (3)

resistor in the resistor. Also have the resistor bank

(1) (2) resistor and resistor; (3) resistor and

on load bank (parallel connection).

Load bank is used for 25 amp. (to 40 amp.)

Started up both 25 amp. resistor bank up to 25 amp.

(about 4,000 ampere): started up rotating brush (about

as yet no current in it); and put about 5 amp. through out-

put brush assembly. Total voltage as observed to be

from resistor-to-resistor bank is no current. In fact

resistor showed about 100 amp. and 100 amp. to be in

resistor. In probing with ohmmeter, noted resistance of

rotating brush had dropped from about 700 ohm (later to

resistor bank) to 20 ohm. This is no resistance, and

rotationally about 100 amp. and 100 amp. to be in

very low value, say 10 ohm.

With the 5 amp. (about) through the resistor bank in the

rotator and also started out, noted about a 10-amp. to

resistor the carbon resistor. This would be the same as

All four brushes in series.

At this point there was a 10-amp. resistor bank in the

station. Secured for 10 amp. It was about 100 ohm

to a resistor in the station. It was about 100 ohm

brush bank.

During actual contact of brush with resistor, resistor

brush bank will be about 10 ohm, say 10 ohm.

1 MAY 1952

Installed voltage probes, ~~as shown by sketch on Page 36~~. Some adjustment appears necessary: voltage fluctuates $\pm .2v$. May be due to carbon brush irregularities. Still have not used mercury, although obtained 5# jug of Hg and funnel and graduate from Professor Reynolds of Chemistry Department.

Device ran satisfactorily--was on only 10-15 minutes. Ran current up to about 12 amps; brass slip rings may develop a squeal and they seemed to get quite hot for such a short run.

Believe voltage probes will be satisfactory. Next plan to run in carbon brushes for an hour or so.

2 MAY 1952

Voltage probes proved unsatisfactory; marked tendency to cut into shaft.

3 MAY 1952

Tried brass spring leaf bearing on brass slip ring. Might be satisfactory if spring leaves were longer; riding on edge (side) of slip rings, there is too much relative velocity. Electrician's Mate 1/C Hull suggested use of twin-brush recorder to permit comparison voltage fluctuations due to carbon brushes and those due to brass spring leaf contacts. Set up brush apparatus but did not have time to make it function properly.

There is a fair amount of random voltage fluctuation across the carbon brushes; there is even more across the brass springs. At this point it appears steady voltages will not be attainable. Possibly a better fit of the carbon brushes will reduce the fluctuations.

7 MAY 1952

Removed stiff brass voltage pickoffs and replaced with longer, less-stiff, brass spring leaf pickoffs. Made it possible to reduce relative velocity at point contact by moving this point closer to center of rotation. Still, however, had voltage fluctuations ± 0.4 volt on a 2-volt max. Sanded contacts and brass slip-ring. Also re-sanded one set of carbon brushes. Not much effect.

Decided to fill contact race with carbon smudge from the slip-ring--there was an immediate reduction to negligible proportions of the voltage swing about a stable value. This stability resulted for both voltages: that taken from the slip-ring and that taken across the entire carbon brush assembly in series. With the arrangement for the brush run-in (all four sets in series), the voltmeter on the slip-rings was reading the drop across the two center sets of the series. It should have, therefore, read $\frac{1}{2}$ the voltage across the entire set, which it did to a reasonable degree. A maximum current of about 10-12 amperes was put through the four carbon brush sets in series for about two hours. It was observed that the brush drop was largely independent of current and somewhat of speed, rising somewhat

with speed. It was also observed that the driving motors slowed down when current through the brushes was reduced or interrupted, coming quickly up to original speed when current was again turned on. The effect was an immediate and easily noticeable one.

The device was run up to about 6,000 rpm on each end for several minutes at a time. It is believed alignment, lubrication, stability, control, rigidity, temperature rise are now satisfactory for actual test runs with mercury.

The fluid brush shunt was removed; strobotacs, voltmeters, ammeter, etc. were made ready. Next plan to add mercury and record data. Be sure to provide two ventilating fans.

8 MAY 1952

Poured 10 cc. of Hg into cylinder. Measured resistance (about 30 ohms). Started rotation, relative velocities up to several thousand rpm. Resistance variable, but very much greater than 30 ohms. It appeared after several minutes of rotation that the resistance was almost that of an open circuit. After several minutes of rotation, although the shaft thermometers were steady at about 45°C, the cylinder was almost too hot to touch.

On the idea that there was insufficient area of contact due to rotation holding the Hg on the inside periphery of the cylinder and away from the disc, 5.5 cc. more of Hg were added to the cylinder. This dropped the static re-

with some. It was also observed that the engine was
shaking down when the engine was started. It
was also observed that the engine was shaking down when
the engine was started. The engine was also shaking down
when the engine was started.

The engine was run up to about 1,000 rpm on road and for
several minutes at a time. It is believed that the engine
was running at a normal speed, and that the engine was
running at a normal speed. The engine was also running at a
normal speed. The engine was also running at a normal speed.
The engine was also running at a normal speed. The engine was
also running at a normal speed. The engine was also running at a
normal speed. The engine was also running at a normal speed.

TEST 1333

Run on 100% of the engine. The engine was running at a
normal speed. The engine was running at a normal speed. The
engine was running at a normal speed. The engine was running
at a normal speed. The engine was running at a normal speed.
The engine was running at a normal speed. The engine was
running at a normal speed. The engine was running at a normal
speed. The engine was running at a normal speed. The engine
was running at a normal speed. The engine was running at a
normal speed. The engine was running at a normal speed. The
engine was running at a normal speed. The engine was running
at a normal speed. The engine was running at a normal speed.

The engine was running at a normal speed. The engine was
running at a normal speed. The engine was running at a normal
speed. The engine was running at a normal speed. The engine
was running at a normal speed. The engine was running at a
normal speed. The engine was running at a normal speed. The
engine was running at a normal speed. The engine was running
at a normal speed. The engine was running at a normal speed.
The engine was running at a normal speed. The engine was
running at a normal speed. The engine was running at a normal
speed. The engine was running at a normal speed. The engine
was running at a normal speed. The engine was running at a
normal speed. The engine was running at a normal speed. The
engine was running at a normal speed. The engine was running
at a normal speed. The engine was running at a normal speed.

sistance to about 20 ohms, but appeared to have no effect in reducing the dynamic resistance. Again, high heat was noted on the cylinder perimeter with cool shafts.

It is possible there was enough oil film in the cylinder to cause an insulating effect. (There was no cleaning fluid available in the lab upon assembly to remove all oil.) It is possible there will be slight amalgamation with time, sufficient to break down the high resistance effect. It is also possible that introduction of a fairly heavy current through the brush will reduce the high resistance.

It was noted that the cylinder motor came up to speed much more easily with the disc motor off, indicating a good deal of friction between the low carbon steel and the mercury.

No leaks were noted. Cylinder was secured with filler plug down to test for leaks overnight.

Next plan to shift pulleys such that can have very low rpm on disc and cylinder--possibly introduce current next time.

9 MAY 1952

No Hg leakage overnight. Shifted to low speed pulleys. Static resistance about 25 ohms. Ran the device, turned brush current on. Used varying amounts of current up to 12 amps. Carbon brush drop fairly steady at about 2-2.5 volts; mercury drop steady--1.5-.5 (fluctuates). Stopped device, measured static resistance (about 2 ohms). Upon letting machine set idle for 10-15 minutes, static

stationed in about 20 days, but according to some reports
in relation to the 1940s and 1950s. It is not clear
what on the 1940s and 1950s. It is not clear
It is possible that the 1940s and 1950s are the same
but to some on the 1940s and 1950s. It is not clear
This is possible in the 1940s and 1950s. It is not clear
all. It is possible that the 1940s and 1950s are the same
with the 1940s and 1950s. It is not clear
effect. It is possible that the 1940s and 1950s are the same
heavy effort through the 1940s and 1950s. It is not clear
resistance.

It was noted that the 1940s and 1950s are the same
much more easily with the 1940s and 1950s. It is not clear
kind of relation between the 1940s and 1950s. It is not clear
to some on the 1940s and 1950s. It is not clear
play down to the 1940s and 1950s. It is not clear
kind of relation between the 1940s and 1950s. It is not clear
run on the 1940s and 1950s. It is not clear
time.

JULY 1943

No 1940s and 1950s. It is not clear
static resistance about 20 days. It is not clear
over contact on. It is not clear
to some. It is not clear
with the 1940s and 1950s. It is not clear
with the 1940s and 1950s. It is not clear
with the 1940s and 1950s. It is not clear

resistance built back up to 25 ohms. There is an immediate drop in resistance once current is turned on and the resistance is variable such that the voltage drop is constant and independent of current. Voltmeter fluctuations are believed to be caused by imperfect voltage pick-offs and carbon brush contacts. Plan next to take data.

12 MAY 1952

Some Hg leakage, 1 drop, due to loose pressed paper insert between disc shaft and cylinder. Tightened two hold-on screws; (should have had four or more of these screws.) Estimate now have about 15.5, (.3, .4) cc. Hg in cylinder.

Measured static resistance, 16 ohms. Ran device without current; measured static resistance again, 3.5 ohms. Device still exhibits immediate resistance drop when current turned on; voltage drop still independent of current.

Took data, listed as Test No. 1. The "average" column is not necessarily the arithmetic average of the maximum and minimum readings, but is rather the value at which the needle appeared to want to indicate. Each reading consumed about 5 minutes in order to permit something approaching "steady-state."

14 MAY 1952

Ran tests No. 2 through 4. Brush current up to 48 amperes; relative rpm up to 1400.

15 MAY 1952

Ran tests No. 5 through 7. Current up to 48 amps;

relative rpm up to 2500. Voltage drop across carbon and mercury remain largely independent of current but shows slight increase (.2 volt) as the temperature rises to 100°C. One hundred degrees C. has been taken as an arbitrary upper limit since this temperature is being read at the center of the Hg brush, whereas the hot-spot seems to be on the cylinder periphery. Care is being taken to avoid flashing the mercury into poisonous vapor which would occur if the Hg temperature were to rise to 357°C, STP. All bearings run cool to the touch. The brass slip rings are too hot to touch, as is the cylinder.

16 MAY 1952

Ran Tests No. 8 and 9, (48 amps, 3500 rpm). Limited to 48 amps by current density of carbon brushes. Carbon brush contact surface is

$$4 \times \frac{5}{16} \times \frac{3}{4} = \frac{60}{64} \text{ in.}^2 ; \quad \frac{48 \text{ amps}}{60/64} = 50 \text{ amps/in.}^2$$

Actually, I believe mercury can carry much greater currents with proper cooling provided. Have not computed Hg current density, but believe it to have reached only some 5 to 10 amps/in.²

17 MAY 1952

Conducted no formal tests, but ran device at about 3,000 rpm, relative and 5 amps from about 1030 steadily until 1630 (6 hrs.) as part of Armed Forces Day exhibit.

1997

$$A = \frac{1}{2} \left(\frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \right) = \frac{1}{2\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$$

SHI YAN 51

Temperature cylinder about 55°C.; discs, 60°C; carbon voltage about 3.2v; Hg voltage about 0.5 v all day. Both voltages steady.

19 MAY 1952

One drop of Hg leakage. Estimate 15 cc. Hg still in cylinder. Static resistance equals 40 Ω ; dynamic R = 5 Ω . Ohmmeter Weston Model 665, type 3, Serial 041058. Ambient 27°C.

Ran tests No. 10 through 15. Noted disc end becoming quite hot and noted in connection with it that pressed paper insert around shaft at cylinder (mercury seal) seemed to be binding on shaft. Again used up to 48 amps, rpm up to 6,000 with 6,500 rpm for a short duration. Greased seal again.

Also noted cylinder slinging Hg through threaded joint, apparently as a result of heat expansion and centrifugal force at 3,000 rpm. Estimate 14.5 cc. of Hg remaining in cylinder.

Indications are that tests should possibly be at test rpm and maximum current (48 amps) from a cold start with ~~them~~ then a temperature-time curve taken to estimate how close to temperature stability device is approaching before one or other of thermometers reach 100°C.

507 100 000

20 MAY 1952

Started device; temperature on disc end jumped to 70°C. Packed grease about pressed paper seal. Secured after a 5-minute run. No leakage apparent. Static resistance on order of 20-40 ohms; ohm meter appeared unstable.

21 MAY 1952

Ran tests No. 16, 17, 18. One drop leakage. Where greasing was of some help, effect quickly wore off at 3500 rpm and disc end again began to show excessive temperature. Repacked seal with grease.

22 MAY 1952

Assisted Prof. Polk in calibrating voltmeters used to obtain carbon and mercury drops; meters very good.

23 MAY 1952

Ran Test No. 19. First assisted Prof. Polk in calibrating ammeter used to obtain brush current; both accurate to high degree.

Reversed polarity on brush; i.e., made disc (+), cylinder (-). Also reduced carbon brush pressure to the minimum. Drive belts appear to be showing effect of wear. Still have binding at pressed-paper insert causing excessive heating.

24, 25 MAY 1952

Reducing data, drawing curves, computing.

2017-11-10

NOTES

2017-11-22

575.1.33

067 1980-81

Calculated minimum Hg contact surface; found it to be 6.11 in.² compared to only 15/16 in.² for carbon. Maximum Hg density (48 amps) = 7.85 amp/in.² compared to 51.15 amp/in.² for carbon. ^{de}Conclusions have been ultra-conservative. Calculations suggest removal of Hg to point just where no leakage can occur on the shaft opening,--the less Hg, the less heat due to friction.

In this connection, also remove paper insert and cut off its flange since ~~it~~ will have no leakage problem, except that seeping through threaded joint. Also solder a bead about the open threads at the shaft side of the cylinder. The combination of drilled core and threads have reduced shaft c/s area at this point to the extent where a hot-spot develops at currents above 40 amps.

Believe above three steps may make possible 10,000 or 12,000 rpm without excessive heating. Also, since load bank will handle 72 amps and DC generator is rated at 59 amps (110v), believe can go to highest available current.

26 MAY 1952

Cut down seal but had to add back some tape to stop Hg slinging. Reduced mercury level to 1 7/32" (1 15/64") above bottom of cylinder exterior. RPM 4,000 each end with no excessive heating. Put solder bead about exposed threads on shaft at cylinder.

Next try reducing Hg level to bottom of exterior seal. Amounts to a reduction of 2cc. from above.

...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...

...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...

...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...

APPENDIX

...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...
...the ... of ...

Threw out enough Hg in running @ 10,000 rpm to place Hg level at bottom of seal exterior by coincidence. Prior to shutting down after Test 22 noted Hg drop as low as .05v with 5 amps, 3,000 rpm each end.

In then attempting to go to 6,000 rpm on each end, encountered excessive vibration and Hg slinging to point where open-circuit developed across mercury brush. Re-filled cylinder to 1 15/64" above bottom of cylinder exterior, and conducted Test No. 23.

At 1600, thermometer in cylinder shaft (tape) came loose and was bent. Straightened; have next to test this thermometer for accuracy in any future tests.

Stopped driving motors; allowed 5 amps. to flow; drop across Hg brush fluctuated 0.4v to 1.1v.

Perhaps possible to conclude mercury is satisfactory as an electrical brush at high rpm (peripheral velocities) if the amount of Hg is kept to a minimum. Course now suggested is to weld threaded joint and to add four more screws or so on seal to obviate any leakage, then fill to Hg level used in 10,000 rpm test. (Hg level 7/8" above bottom exterior of cylinder) and then run device at maximum current (48 or 59 amps) for 1,000 hours or until failure. At this point, remove weld, disassemble, examine for condition of surfaces and of Hg and also amount of Hg left. If still satisfactory, reseal and reweld and run for 1,000 more hours in an altitude chamber.

APPENDIX B

Excerpts From Liquid Metals Handbook

Ref: Liquid Metals Handbook, NavExos P-733, 1 June 1950,
Atomic Energy Commission, Department of the Navy,
Washington, D. C. For sale by Superintendent of
Documents, U.S. Government Printing Office,
Washington, D. C. \$1.25

Page 2: "The pressure created by passing an electric current through a molten metal, in combination with a magnetic field, offers a solution to the problem of pumping these metals." (i.e., molten Al, Zn, Cu, etc.) Pumping head only 1 to 2 feet (p. 5).

Page 5: The present (1950) uses of liquid metals do not list electric current conduction through a moving contact.

Page 9: Hg boiler tubes are made from Sicromo 5S steel (0.12 C, 0.5 Mo, 5.0 Cr, 1.5 Si) which has a very low solubility in Hg. The use of .000005 to .001 per cent *titanium* and .002 per cent Mg in the Hg assures that Hg wets steel and reduces solubility of tube metal (950°-1050° F). 18-8 stainless also good.

Page 11: "A pipe filled with Na was used as a bus bar for carrying 4000 amps of DC current by Dow Chemical CO." (See Boundy, R. H., Trans. Electrochem. Soc. 62, 151 (1932), Sodium Bus Bar--A 4000 amps. cond. "Liquid metals are successfully used as 'brushes' in electrical equipment."

Page 12: "Metals are elementary substances and do not

• 1000000

decompose, polymerize, carbonize, etc.

Stainless steel has operated as a hot metal container at 1000°F for 1 year.

Page 79: "Mass transfer in liquid metals may be influenced by electrical effects. Transfer of dissolved elements in solid and in liquid metals under the influence of applied potentials, referred to in the literature as electrolytic diffusion, has been observed and studied quantitatively. See also Von Kreman, R., "Electrolysis of Molten Alloys," Sammlung Chemischer und Chemisch-Technischer Vortraege 28, 347-408, 1926. For example, a direct potential of 5 volts with a flow of 20 amperes for periods of less than a day resulted in transfer of microscopic amounts of carbon in gamma iron. No evidence of mass transfer by this means has been observed so far in liquid-metal-heat transfer systems although there is some evidence that application of a potential can be used to inhibit attack. See also: Barnes, A.H., Smith, F.A., Whitham, G., Direct Current Electromagnetic Pumps, ANL-4322, Oct. 25, 1947.

Markert, W., Jr., and Piotler, E. C., B & W Repr. No. ES-401-2. (Project "Baby," NObs-34222), June 9, 1947

Markert, W., Jr., and Piotler, E. C., B & W Repr. No. ES-401-1. (Project "Baby," NObs-34222), April 17, 1947.
Rehn, I, ANL-4029, Sept. 2 1947

"Symposium on Basic Properties of Liquid Metals" held at ANL on April 5, 1949.

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

... ..

Page 80: "Attack on steels by mercury is completely (rate of attack less than 1 mil per year) inhibited by the addition of titanium or zirconium. These inhibitors were found after very extensive and expensive laboratory investigations and though possible explanations have been offered, the mechanism by which they act is not known. Where oxygen is known to accelerate attack by liquid metals, inhibitors are being sought which will tie up the oxygen as an insoluble oxide."

Page 82: "Low-carbon steels have good resistance to attack by flowing Hg below about 400°C (752°F)."

Page 85: "Attack by Hg on ferrous alloys can be reduced to negligible amounts by the addition of an inhibitor to the mercury, the best of which is Ti. In order to insure good heat transfer and to prevent excessive use of the inhibitor, it is also necessary to add a ^{wetting} ~~melting~~ agent, the best of which is magnesium." See also: Hacket, H. N., "Mercury for the Generation of Light, Heat and Power," Trans. of the ASME, Oct. 1952, p. 647.

Page 86: Add to .0001-.001 per cent Ti, or .04-.02 per cent Zr.

"Copper in Hg increases its attack on low-C steel."

"In addition to an inhibitor it was found desirable to have a ^{wetting} ~~melting~~ agent present in the Hg. Its function is two-fold:

Page 10: ...
(...)
...
...
...
...
...
...
...

Page 11: ...
...

Page 12: ...
...
...
...
...
...
...
...
...

Page 13: ...

...
...
...
...

to reduce oxides on steel^e surfaces so that ~~melting~~^{wetting} and optimum heat transfer may be realized; and to react with the free oxygen, nitrogen and water vapor in the Hg in order to keep the inhibitor active. Wetting agents must, therefore, have a greater affinity for O₂ and N than both the inhibitor (Ti) and iron."

"Mg has been found effective as a wetting agent with no deleterious effects. Use 20 ppm."

Page 87: "Wolfram, molybden^um, chromi^uum and beryllium can be considered for longtime use as containers of Hg at elevated temperatures."

Silver solder (Ag-Cu-Zn) was drastically attacked on exposure to Hg for 24 hours at 400°C."

"Carbon is negligibly soluble in Hg."

to provide better on staff support in that regard. The entire
staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.
The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.
The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.

"The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff."
The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.
The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.
The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.
The staff is responsible for the quality of the work and the
quality of the work is the responsibility of the staff.





OCT 2
FEB 26
MAY 20
NOV 24
22 DEC 65

BINDERY 2
RESERVE
DISPLAY
14213

Thesis
S49

Shults

An investigation of mercury as a high-speed electrical contact. 1952.

OCT 2
FEB 26
MAY 27
APR 10
MAY 19
JUN 5
NOV 24
22 DEC 65

BINDERY 2
RENEWED
RENEWED
RENEWED
RENEWED
RESERVE
DISPLAY
14213

18057

Thesis
S49

Shults

An investigation of mercury as a high-speed electrical contact. 1952.

Library
U. S. Naval Postgraduate School,
Monterey, California

18057

thesS49

An investigation of mercury as a high-sp



3 2768 000 99793 6

DUDLEY KNOX LIBRARY